



## AMERIPOLISH Technical Data Sheet

Ameripolish, Inc.  
120 Commercial Ave.  
Lowell, AR 72745-8725

800.592.9320  
479.725.0033  
Fax: 479.725.0031

### PRODUCT: AMERIPOLISH® STRIP & CLEAN

*Strips sealers to open concrete for acceptance of Ameripolish color products and finishes*

**DESCRIPTION:** The AmeriPolish solvent and water-based dyes are formulated using extremely fine molecules of color designed to penetrate and color any cementitious surface (All bond barriers must be removed prior to dye application). AmeriPolish dye was created for use with polished concrete, but can also be used as a base color or touch up for concrete that has received integral color, dry shake hardeners, acid stains or even as an overlay to itself. Even after being densified and polished, concrete is porous and densifiers take 2-6 months to achieve their full repellency so AmeriPolish created the Ameripolish WB Surface Sealer for protection of your dyed and polished floor, and now we offer the Ameripolish® Strip & Clean for those times when it is necessary to remove the Stain Shield in order to change or enhance your dye color. Prior to starting your project, always apply the dye to a sample area at the actual site in order to confirm that the floor is receptive to dye, and to establish the desired color. **REMEMBER that dyes will not mask or hide imperfections in the floor, and may appear different in areas that received different pours or patches.** The addition of the Ameripolish® Strip & Clean is an integral component of the AmeriPolish System.

#### USES:

Ameripolish® Strip & Clean is a water-based stripping agent specially formulated for the removal of the Ameripolish WB Surface Sealer from polished concrete floors that have received the AmeriPolish dyes. It is not uncommon for an owner or architect to ask for project changes following the completion of the dye and Ameripolish WB Surface Sealer application, and prior to the formulation of the Ameripolish® Strip & Clean, it was necessary to grind off Stain Shield in order to apply additional dye or dye colors.

#### BENEFITS:

Provides the opportunity to remove Stain Shield without having to use diamond grinders.

#### MIXING:

Ameripolish® Strip & Clean is provided in ready-to-use 5 gallon containers. Agitate just prior to application.

#### PREPARATION:

Thoroughly clean the surface that is to receive the Ameripolish® Strip & Clean in order to remove any abrasive materials that may scratch the surface during the burnishing stage.

#### COVERAGE RATE:

Ameripolish® Strip & Clean will cover approximately 400-600 square

feet per gallon per application, depending on number of Stain Shield applications are to be removed.

#### APPLICATION:

Ameripolish® Strip & Clean is best applied with the Patriot Sprayer System utilizing the #8 grey tip. Apply in an even coat ensuring that the entire surface is wetted, but without puddling. Following a well time of 5-10 minutes, the floor will begin to turn a milky white, indicating that the Ameripolish® Strip & Clean and Stain Shield are properly reacting. At this time, it is necessary to scrub the floor with a Black 3M pad on a floor scrubber. Rinse and clean the floor, removing all material from floor. Dispose of waste according to local regulations. If sporadic areas of the Stain Shield still remain, repeat the process until all material is removed.

#### PRECAUTIONS:

Following the successful re-application of dye, or simply having to have fixed a faulty Stain Shield application, it is necessary to provide a clean and dry floor prior to the re-application of Stain Shield. Follow all Stain Shield application instructions.

#### Safety Precautions:

Before using Ameripolish® Strip & Clean, read the MSDS and instructions for use. Use good hygiene when handling this product. Wash hands and any areas that come into direct contact with this material.

#### WARRANTY:

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. **Applicator is responsible for testing material for effectiveness and performance.** Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective.

#### MANUFACTURER:

Ameripolish, Inc.

#### STORAGE:

Store in safe place. Keep containers tightly sealed. Do not allow product to freeze, nor use product if it has been frozen.





# AMERIPOLISH Technical Data Sheet

Ameripolish, Inc.  
120 Commercial Ave.  
Lowell, AR 72745-8725

800.592.9320  
479.725.0033  
Fax: 479.725.0031

## PACKAGING SPECIFICATIONS:

### Product Name – Ameripolish Strip & Clean

Product #	Shipping Wt.	Container(s)
SS5	10 lbs.	1 Gal. Plastic Bottle – Makes 5 Gal.
SS25	50 lbs.	5 Gal. Plastic Bottle – Makes 25 Gal.

## HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS):

Health	3	Flammability	0	Reactivity	0
0 – Least, 1 – Slight, 2 – Moderate, 3 – High, 4 – Extreme					

