



Q-28 & Q-11 DUR-A-QUARTZ AGGREGATE

DESCRIPTION

Q-28 DUR-A-QUARTZ is a colored, naturally rounded, translucent quartz aggregate produced specially for seamless polymer flooring applications. The very hard quartz granules are sieved for a selected size range and colored with high quality pigments, which are ceramically bonded to the clear quartz surface. This special coloring process provides superior resistance to solvents, acids and chemicals used to formulate epoxies and other type binders. The translucence of the quartz allows the color from the back side of the granule to be reflected through the granule. If the surface color is worn off mechanically by traffic, this translucence allows the abraded granules to retain its color.

Q-11 DUR-A-QUARTZ is a colored aggregate produced specifically for seamless polymer flooring where a high degree of slip resistance is desired. The base material is a naturally formed, semi-angular, very hard quartz granule. The material is cleaned, dried and sieved for a selected size range. It is then colored with high quality pigments that are ceramically bonded to the surface.

COLORS

DUR-A-QUARTZ decorative aggregate is available in blended solid colors and in two sizes. Color options are standard colors and custom color blends. Please refer to the Quartz Color Selector Chart.

SIEVE ANALYSIS

(Typical Analysis- Not Specifications)

<u>U.S.</u> <u>Mesh</u>	<u>Q-28</u> <u>Quartz</u>	<u>Q-11</u> <u>Quartz</u>	<u>Special</u> <u>Bond</u>
16	---	0.4	---
---	---	---	---
20	<1	76	---
30	23	15	---
40	70	3	3.0
50	6	1	21.5
70	<1	<1	34.1
100	---	---	28.3
140	---	---	11.0
200	---	---	1.9
270	---	---	0.1

(Typical Analysis- Not Specifications)

HARDNESS 6.5 - 7 on Moh's Mineral Scale

POROSITY less than 2.0%

MOISTURE CONTENT less than 0.5%

PACKAGING 50 lbs. in plastic bags

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN. Before using any Dur-A-Flex products, be sure the Material Safety Data Sheet is read and understood.

Before using any Dur-A-Flex, Inc. product, be sure the Material Safety Data Sheet is read and understood.

"Warranties: Seller warrants that its goods, as described on the face hereof, are free from any defects in material or workmanship. SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. SELLER SHALL NOT BE LIABLE FOR PROSPECTIVE PROFITS OR SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES. Seller's sole liability and buyer's exclusive remedy for breach of any warranty as expressly limited, at seller's option, to replacement at the original F.O.B. point or refund of purchase price, but in no event will Seller's liability exceed the total purchase price of the defective product. Seller shall not be responsible for any claim resulting from failure to utilize product in the manner in which it was intended and in accordance with instruction provided for use of product. Any claim for breach of warranty shall be deemed waived unless buyer shall give seller written notice of such claim within sixty (60) days after delivery and shall allow seller reasonable opportunity to investigate claim and inspect product."