# Material Safety Data Sheet ARDEX FDM Full Depth Repair Mortar with CI

## Section I - Manufacturer's Information

identity.	ARDEX FDM Full Dept	n Repair Mort	ar with Cl	Common Name/Synor	iym: Polymer Modifie Corrosion Inhibite	d Cementitious Based Re or	epair Mortar wit	
Manufacturer's Name:	400 Ardex Park Drive Emergency #		Emergency #:	(724) 203-8499 (800) 255-3924 1-813-248-0585		ass: Not Regulated ber: Not Registered		
Section	II - Preparatio	on Inforr	nation					
Prepared By:	Research & Development				Date Prepared: January 29, 2010			
Section	III - Hazardou	s Ingrea	dients					
Component -	A	Percent			TWA/TLV			
Ingredient		w/w	CAS Number	OSHA	ACGIH	Other	LD50 LC5	
Calcium Sulfate		1-5	7778-18-9	15.0 mg/m³	10.0 mg/m <sup>3</sup>	N/E mg/m <sup>3</sup>	N/E N/E	
Silicon Dioxide Portland Cement		40-70 10-30	14808-60-7 65997-15-1	10/(%SiO2+2) mg 5.0 mg/m³	/m <sup>3</sup> 0.10 mg/m <sup>3</sup> 10.0 mg/m <sup>3</sup>	NIOSH 0.05 mg/m <sup>3</sup> N/E mg/m <sup>3</sup>	N/E N/E N/E N/E	
				Ŭ				
Section	IV - Physical/	Chemic	al Charac	teristics				
Component	- A							
Boiling Point:			orDensity [Air=1]		por Pressure: N/A		9.0 - 12.0 su	
Molting Doint:			n Rate [Ether=1]		hysical State: Solid	Solubility in Water:	Miscible	
Melting Point:	int: N/A Specific Gravity: [H2O=1 arance and Odor: Gray Powder- Slight Odor			: > <b>1.0</b> Oc	Odor Threshold: <b>N/A</b> Coefficient of Water/Oil Distribution: <b>N/A</b>			
Freezing Point:	nce and Odor: Gray Pow	der- Silgin O						
Freezing Point: Appearar	nce and Odor: Gray Pow	-		Data				
Freezing Point: Appearar	V - Fire and E	-		Data				
Freezing Point: Appearar Section Component	V - Fire and E	-	n Hazard	Data Point: N/A		Autoignition Temper	ature: <b>N/A</b>	
Freezing Point: Appearar Section Component Flamma	V - Fire and E	-	n Hazard	Point: <b>N/A</b>	Sensiti	Autoignition Temper vity to Static Discharge: <b>N</b>		
Freezing Point: Appearar Section Component Flamma	• V - Fire and E - A ability: N/A /UEL: N/A - N/A	-	n Hazard	Point: <b>N/A</b>	Sensiti Special Firefighting	<b>U</b> 1		
Freezing Point: Appearar Section Component Flamma Limits LEL Hazardous Dec	• V - Fire and E - A ability: N/A /UEL: N/A - N/A composition Products: COx, NOx, F	Explosio	n Hazard Flash Sensitivity to i	Point: <b>N/A</b>	Special Firefighting	<b>U</b> 1	one	
Freezing Point: Appearar Section Component Flamma Limits LEL	• V - Fire and E - A ability: N/A /UEL: N/A - N/A composition Products: COx, NOx, F	Explosio	n Hazard Flash Sensitivity to i	Point: <b>N/A</b>	Special Firefighting Procedures:	vity to Static Discharge: N	one ar	

## Section VI - Reactivity Data

Component - A Hazardous Decomposition Products: N/A Hazardous Polymerization: N/A				Stability: Stable		Incompatibility	Incompatibility (Materials to Avoid): Conditions to Avoid:		•	
Section VII -	Health Ha	zard I	Data							
Carcinogenicity:	Yes NTP:	Yes	IARC: 0	Grp. 1	OSHA Reg	ulated: <b>No</b>	LD50: N/A	LC50:	N/A	
Effects and Hazards of Eye Contact: Effects and Hazards of Inhalation (Breathing):		ns silica (e	quartz) dus	st, which has	been designat		i group 1- human c ijury such as silico		rolonged	
Effects and Hazards of Skin Contact: Effects and Hazards of Ingestion (Swallowing):	May cause som	e stomac	h distress.							
HMIS	Health:	1	Flamm	ability	0	Reactivity:	0 PPE:	J		

Page 1 of 2

# **Material Safety Data Sheet**

ARDEX FDM Full Depth Repair Mortar with CI

#### Section VIII - Emergency and First Aid Procedures

Treatment for Eye Contact:	As with any foreign material in the eyes, they should be flushed for fifteen minutes with running water while holding the eyes open. This will assist in flushing material from the eye. If irritation continues, seek medical attention.
Treatment for Inhalation (Breathing):	If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention
Treatment for Skin Contact:	Wash with mild soap and water. Hand creams should be used to prevent dry skin. If skin irritation, reddening or a rash occur, seek medical attention.
Treatment for Ingestion (Swallowing):	Contact medical help immediately; untrained first aid personnel should not attempt to administer first aid.

### Section IX - Precautions for Safe Handling and Use

particular use.

Steps to be taken in case material is released or spilled (Dry Stage):	Sweep and dispose of in proper receptacle.
Steps to be taken in case material is released or spilled (Wet Stage):	Scoop into proper receptacle and allow to harden.
Waste Disposal Method:	Per local, state and federal regulations.
Precautions To Be Taken In Handling and Storing:	Store in a cool, dry location out of direct sunlight.
Other Precautions:	This material is an industrial product designed to be used by professionals familar with the requirements of this material safety data sheet.
Respiratory Protection:	Respiratory protection is is recommended for mixing this product. Respiratory protection is not required for normal use of this product. When material is mixed, ground upon or sanded when it is dry, NIOSH/MSHA approved respirators for silica (quartz) dust should be provided and worn. All workers required to use respiratory protection should be trained in their proper selection, use and care.
Ventilation:	Recommended; local or mechanical when mixing, applying or sanding the product in the dry state.
Protective Gloves:	Recommended; plastic or rubber.
Eye Protection:	Recommended; chemical splash safety goggles.
Other Protective Equipment:	Recommended; spalsh bib and protective clothing.
Work and Hygienic Practices:	Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or smoking.
California Proposition 65:	This product contains crystalline silica (quartz sand), which is considered a carcinogen by the State of California.

The information and recommendations contained herein are, to the best of ARDEX' knowledge and belief, accurate and reliable as of the date issued. ARDEX does not warrant or guarantee their accuracy or reliability, and ARDEX shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its