

**DUR-A-FLEX**
INNOVATION FROM THE FLOOR UP

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

**Material Safety
Data Sheet**

Date Prepared 8/2/2014

SECTION I - IDENTIFICATION		HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	2
IDENTITY (As Used on Label) Cryl-A-Color: all colors			Flammability	1
COMMON NAME Acrylate Pigmented Dispersions			Reactivity	1
			Personal Protection	G
SECTION II - PRODUCT COMPONENTS		CAS.#	OSHA PEL	ACGIH TLV
Titanium Dioxide		13463-67-7	15mg/m ³	10mg/m ³
Aluminum Hydroxide		21645-51-2	10mg/m ³	2mg/m ³
Amorphous Silica		7631-86-9	80mg/m ³	10mg/m ³
Inorganic Iron Oxides		1309-37-1	15mg/m ³	10mg/m ³
1,6-Hexanedioldiacrylate		13048-33-4	N.E. ¹	N.E.
Tripropylene Glycol Diacrylate		42978-66-5	N.E.	N.E.
¹ N.E. = None Established				
T.S.C.A. Status - O.K. on all above components.				
FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300				
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS				
Boiling Point °F	N/A	Specific Gravity (H ₂ O = 1)	>1	
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A	
Vapor Density (AIR = 1)	N/A	Flash Point (Butyl Acetate = 1)	N/A	
Volatile Organic Compounds (VOC) = Zero grams/liter				
Solubility in Water: Negligible				
Appearance and Odor: Powder of specified color with no odor				
SECTION IV - FIRE and EXPLOSION HAZARD DATA				
Flash Point (Closed Cup Method)	213°F	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media Use CO ₂ , foam, dry powder or cover with sand				
Special Firefighting Procedures				
Evacuate enclosed and surrounding areas. If smoke and fumes cannot be avoided, use proximity suit and self-contained breathing apparatus. Use water spray to cool containers and disperse vapors. Keep spills away from sources of ignition.				
Unusual Fire and Explosion Hazards: Vapor is heavier than air and forms explosive mixture with air. Never use welding or cutting torch on or near containers or drums (even when empty). Product residue or vapor in drum or container can ignite explosively.				
SECTION V - REACTIVITY DATA				
Stability	Unstable		Conditions to Avoid	
	Stable	X	Keep containers closed when not in use.	
Incompatibility (Materials to Avoid)		Reducing agents, Oxidizing agents, solid polymeric particles		
Hazardous Decomposition or Byproducts: Thermal decomposition may produce oxides of carbon, nitrogen, and sulfur				
Hazardous Polymerization	May Occur		Conditions to Avoid: High temperatures, oxygen-free atmospheres, or contaminated	
	Will Not Occur	X	areas. Avoid contact with peroxides, azocompounds and redox systems.	

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin, nose throat and lungs, eye irritation.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin, eyes, nose, throat, lungs, shortness of breath.

CHRONIC - Repeated overexposure will cause severe skin irritation, dermatitis and sensitization.

Sensitized persons may experience rapid irritation of skin upon exposure.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - If person is conscious, give water or milk to dilute stomach contents.

Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH/MSHA Approved respirator.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves	Natural rubber or Neoprene.	Eye Protection	Splash goggles or face shield.
-------------------	-----------------------------	----------------	--------------------------------

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Establish good personal hygiene and work practices. Always wash hands and face before eating, drinking or smoking.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Wear protective equipment to prevent exposure.

Eliminate all sources of ignition. Scoop or vacuum up, place in closed container in accordance to Resources Conservation and Recovery Act (RCRA), and in accordance with federal, state and local regulations.

Waste Disposal Method:

Dispose in accordance with Federal, State and Local requirements.

Other Precautions NONE KNOWN.

Prepared By: Murty Bhamidipati - Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."