

**MATERIAL SAFETY DATA SHEET**GP3505A53  
09 00DATE OF PREPARATION  
Feb 11, 2015**SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION****PRODUCT NUMBER**

GP3505A53

**PRODUCT NAME**

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Charcoal

**MANUFACTURER'S NAME**THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115**Telephone Numbers and Websites**

<b>Regulatory Information</b>	(216) 566-2902 www.paintdocs.com
<b>Medical Emergency</b>	(216) 566-2917
<b>Transportation Emergency*</b>	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

**SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS**

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	100-51-6	<b>Phenylmethanol</b> ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	<b>4-Nonylphenol</b> ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	<b>Alkyl Glycidyl Ether</b> ACGIH TLV OSHA PEL	Not Available Not Available	
7	15625-89-5	<b>Trimethylolpropane Triacrylate</b> ACGIH TLV OSHA PEL	Not Available Not Available	
61	25085-99-8	<b>Epoxy Polymer</b> ACGIH TLV OSHA PEL	Not Available Not Available	
5	13463-67-7	<b>Titanium Dioxide</b> ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	
0.7	1333-86-4	<b>Carbon Black</b> ACGIH TLV OSHA PEL	3.5 MG/M3 3.5 MG/M3	

**SECTION 3 — HAZARDS IDENTIFICATION****ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

**EFFECTS OF OVEREXPOSURE****EYES:** Causes burns.**SKIN:** Causes burns.**INHALATION:** Irritation of the upper respiratory system.**HMIS Codes**

<b>Health</b>	3*
<b>Flammability</b>	1
<b>Reactivity</b>	2

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and laundry before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES****FLASH POINT**

> 200 °F PMCC

**LEL**

Not  
Applicable

**UEL**

Not  
Applicable

**FLAMMABILITY CLASSIFICATION**

Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.60 lb/gal	1150 g/l
<b>SPECIFIC GRAVITY</b>	1.16	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.34 lb/gal	41 g/l
	0.34 lb/gal	41 g/l
	Less Water and Federally Exempt Solvents	
	Emitted VOC	

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
1333-86-4	Carbon Black	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

## SECTION 12 — ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

# MATERIAL SAFETY DATA SHEET

GP3505A54  
11 00

DATE OF PREPARATION  
Apr 15, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NUMBER**

GP3505A54

**PRODUCT NAME**

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Steel Gray

**MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

**Telephone Numbers and Websites**

<b>Regulatory Information</b>	(216) 566-2902 www.paintdocs.com
<b>Medical Emergency</b>	(216) 566-2917
<b>Transportation Emergency*</b>	(800) 424-9300
<small>*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</small>	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	100-51-6	<b>Phenylmethanol</b> ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	<b>4-Nonylphenol</b> ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	<b>Alkyl Glycidyl Ether</b> ACGIH TLV OSHA PEL	Not Available Not Available	
7	15625-89-5	<b>Trimethylolpropane Triacrylate</b> ACGIH TLV OSHA PEL	Not Available Not Available	
60	25085-99-8	<b>Epoxy Polymer</b> ACGIH TLV OSHA PEL	Not Available Not Available	
7	13463-67-7	<b>Titanium Dioxide</b> ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	
0.2	1333-86-4	<b>Carbon Black</b> ACGIH TLV OSHA PEL	3.5 MG/M3 3.5 MG/M3	

## SECTION 3 — HAZARDS IDENTIFICATION

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

**EFFECTS OF OVEREXPOSURE**

**EYES:** Causes burns.  
**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

**HMIS Codes**

<b>Health</b>	3*
<b>Flammability</b>	1
<b>Reactivity</b>	2

In a confined area vapors in high concentration may cause headache, nausea or dizziness.  
Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and laundry before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES****FLASH POINT**

> 200 °F PMCC

**LEL**

Not  
Applicable

**UEL**

Not  
Applicable

**FLAMMABILITY CLASSIFICATION**

Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.72 lb/gal	1165 g/l
<b>SPECIFIC GRAVITY</b>	1.17	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.35 lb/gal	42 g/l
	0.35 lb/gal	42 g/l
	Less Water and Federally Exempt Solvents	
	Emitted VOC	

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
1333-86-4	Carbon Black	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

## SECTION 12 — ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.



# MATERIAL SAFETY DATA SHEET

GP3505A55  
12 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A55

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Bone White

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure	
3	100-51-6	Phenylmethanol	ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol	ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	Alkyl Glycidyl Ether	ACGIH TLV OSHA PEL	Not Available Not Available	
6	15625-89-5	Trimethylolpropane Triacrylate	ACGIH TLV OSHA PEL	Not Available Not Available	
58	25085-99-8	Epoxy Polymer	ACGIH TLV OSHA PEL	Not Available Not Available	
12	13463-67-7	Titanium Dioxide	ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	10.13 lb/gal	1213 g/l
<b>SPECIFIC GRAVITY</b>	1.22	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	3%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
0.32 lb/gal	38 g/l	Less Water and Federally Exempt Solvents
0.32 lb/gal	38 g/l	Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 — TRANSPORT INFORMATION**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

**US Ground (DOT)**

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

**Bulk Containers may be Shipped as:**

UN3066, PAINT, 8, PG III, (ERG#153)

**Canada (TDG)**

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IATA/ICAO**

UN3066, PAINT, 8, PG III

**SECTION 15 — REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 — OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

# MATERIAL SAFETY DATA SHEET

GP3505A56  
10 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A56

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Silver Gray

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure	
3	100-51-6	Phenylmethanol	ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol	ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	Alkyl Glycidyl Ether	ACGIH TLV OSHA PEL	Not Available Not Available	
7	15625-89-5	Trimethylolpropane Triacrylate	ACGIH TLV OSHA PEL	Not Available Not Available	
60	25085-99-8	Epoxy Polymer	ACGIH TLV OSHA PEL	Not Available Not Available	
7	13463-67-7	Titanium Dioxide	ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.75 lb/gal	1167 g/l
<b>SPECIFIC GRAVITY</b>	1.17	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.35 lb/gal	42 g/l
	0.35 lb/gal	42 g/l
		Less Water and Federally Exempt Solvents
		Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 — TRANSPORT INFORMATION**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

**US Ground (DOT)**

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

**Bulk Containers may be Shipped as:**

UN3066, PAINT, 8, PG III, (ERG#153)

**Canada (TDG)**

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IATA/ICAO**

UN3066, PAINT, 8, PG III

**SECTION 15 — REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 — OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.



# MATERIAL SAFETY DATA SHEET

GP3505A59  
10 00

DATE OF PREPARATION  
Feb 24, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A59

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), White

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure	
3	100-51-6	Phenylmethanol	ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol	ACGIH TLV OSHA PEL	Not Available Not Available	
6	15625-89-5	Trimethylolpropane Triacrylate	ACGIH TLV OSHA PEL	Not Available Not Available	
59	25085-99-8	Epoxy Polymer	ACGIH TLV OSHA PEL	Not Available Not Available	
12	13463-67-7	Titanium Dioxide	ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic skin reaction in susceptible persons.

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and laundry before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	10.18 lb/gal	1220 g/l
<b>SPECIFIC GRAVITY</b>	1.23	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.34 lb/gal	41 g/l
	0.34 lb/gal	41 g/l
		Less Water and Federally Exempt Solvents
		Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY**

**STABILITY** — Stable

**CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS****WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

# MATERIAL SAFETY DATA SHEET

GP3505A61  
10 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A61

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Black

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	100-51-6	Phenylmethanol		
		ACGIH TLV	Not Available	0.15 mm
		OSHA PEL	Not Available	
3	84852-15-3	4-Nonylphenol		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
2	68609-97-2	Alkyl Glycidyl Ether		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
7	15625-89-5	Trimethylolpropane Triacrylate		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
63	25085-99-8	Epoxy Polymer		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
2	1333-86-4	Carbon Black		
		ACGIH TLV	3.5 MG/M3	
		OSHA PEL	3.5 MG/M3	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES****FLASH POINT**

> 200 °F PMCC

**LEL**

Not  
Applicable

**UEL**

Not  
Applicable

**FLAMMABILITY CLASSIFICATION**

Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.30 lb/gal	1114 g/l
<b>SPECIFIC GRAVITY</b>	1.12	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
0.33 lb/gal	40 g/l	Less Water and Federally Exempt Solvents
0.33 lb/gal	40 g/l	Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
1333-86-4	Carbon Black	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS****WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.



# MATERIAL SAFETY DATA SHEET

GP3505A62  
11 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A62

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Parchment

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure	
3	100-51-6	Phenylmethanol	ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol	ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	Alkyl Glycidyl Ether	ACGIH TLV OSHA PEL	Not Available Not Available	
6	15625-89-5	Trimethylolpropane Triacrylate	ACGIH TLV OSHA PEL	Not Available Not Available	
59	25085-99-8	Epoxy Polymer	ACGIH TLV OSHA PEL	Not Available Not Available	
9	13463-67-7	Titanium Dioxide	ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.86 lb/gal	1181 g/l
<b>SPECIFIC GRAVITY</b>	1.19	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.34 lb/gal	41 g/l
	0.34 lb/gal	41 g/l

**SECTION 10 — STABILITY AND REACTIVITY**

**STABILITY — Stable**

**CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION**

**CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 — TRANSPORT INFORMATION**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

**US Ground (DOT)**

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

**Bulk Containers may be Shipped as:**

UN3066, PAINT, 8, PG III, (ERG#153)

**Canada (TDG)**

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IATA/ICAO**

UN3066, PAINT, 8, PG III

**SECTION 15 — REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 — OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

# MATERIAL SAFETY DATA SHEET

GP3505A69  
09 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A69

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Royal Blue

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure	
3	100-51-6	Phenylmethanol	ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol	ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	Alkyl Glycidyl Ether	ACGIH TLV OSHA PEL	Not Available Not Available	
7	15625-89-5	Trimethylolpropane Triacrylate	ACGIH TLV OSHA PEL	Not Available Not Available	
61	25085-99-8	Epoxy Polymer	ACGIH TLV OSHA PEL	Not Available Not Available	
5	13463-67-7	Titanium Dioxide	ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.62 lb/gal	1152 g/l
<b>SPECIFIC GRAVITY</b>	1.16	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.34 lb/gal	41 g/l
	0.34 lb/gal	41 g/l
		Less Water and Federally Exempt Solvents Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 — TRANSPORT INFORMATION**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

**US Ground (DOT)**

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

**Bulk Containers may be Shipped as:**

UN3066, PAINT, 8, PG III, (ERG#153)

**Canada (TDG)**

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IMO**

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

**IATA/ICAO**

UN3066, PAINT, 8, PG III

**SECTION 15 — REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 — OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.



# MATERIAL SAFETY DATA SHEET

GP3505A71  
11 00

DATE OF PREPARATION  
Feb 11, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

GP3505A71

### PRODUCT NAME

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Pewter

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### Telephone Numbers and Websites

Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	100-51-6	Phenylmethanol ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	4-Nonylphenol ACGIH TLV OSHA PEL	Not Available Not Available	
2	68609-97-2	Alkyl Glycidyl Ether ACGIH TLV OSHA PEL	Not Available Not Available	
6	15625-89-5	Trimethylolpropane Triacrylate ACGIH TLV OSHA PEL	Not Available Not Available	
59	25085-99-8	Epoxy Polymer ACGIH TLV OSHA PEL	Not Available Not Available	
9	13463-67-7	Titanium Dioxide ACGIH TLV OSHA PEL OSHA PEL	10 mg/m3 as Dust 10 mg/m3 Total Dust 5 mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

### EFFECTS OF OVEREXPOSURE

**EYES:** Causes burns.

**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

### HMIS Codes

Health	3*
Flammability	1
Reactivity	2

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	9.86 lb/gal	1180 g/l
<b>SPECIFIC GRAVITY</b>	1.19	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.34 lb/gal	41 g/l
	0.34 lb/gal	41 g/l
		Less Water and Federally Exempt Solvents
		Emitted VOC

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

# MATERIAL SAFETY DATA SHEET

GP3505A74  
10 00

DATE OF PREPARATION  
Feb 24, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NUMBER**

GP3505A74

**PRODUCT NAME**

GENERAL POLYMERS® 3505 Stipple Epoxy Floor Coating (Part A), Classic Red

**MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

**Telephone Numbers and Websites**

<b>Regulatory Information</b>	(216) 566-2902 www.paintdocs.com
<b>Medical Emergency</b>	(216) 566-2917
<b>Transportation Emergency*</b>	(800) 424-9300
<small>*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</small>	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	100-51-6	<b>Phenylmethanol</b> ACGIH TLV OSHA PEL	Not Available Not Available	0.15 mm
3	84852-15-3	<b>4-Nonylphenol</b> ACGIH TLV OSHA PEL	Not Available Not Available	
1	68609-97-2	<b>Alkyl Glycidyl Ether</b> ACGIH TLV OSHA PEL	Not Available Not Available	
7	15625-89-5	<b>Trimethylolpropane Triacrylate</b> ACGIH TLV OSHA PEL	Not Available Not Available	
58	25085-99-8	<b>Epoxy Polymer</b> ACGIH TLV OSHA PEL	Not Available Not Available	

## SECTION 3 — HAZARDS IDENTIFICATION

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Incidental contact with surfaces, protective equipment, or clothing contaminated with product can cause irritation. Irritation may not be noticeable at time of contact but may occur later.

**HMIS Codes**

<b>Health</b>	3*
<b>Flammability</b>	1
<b>Reactivity</b>	2

**EFFECTS OF OVEREXPOSURE**

**EYES:** Causes burns.  
**SKIN:** Causes burns.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.  
Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the nervous system
- the reproductive system

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic skin reaction in susceptible persons or skin sensitization.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

**SKIN:** Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES**

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
> 200 °F PMCC	Not Applicable	Not Applicable	Not Applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Do not get in eyes or on skin. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

To prevent eye contact, wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

<b>PRODUCT WEIGHT</b>	9.94 lb/gal	1190 g/l
<b>SPECIFIC GRAVITY</b>	1.20	
<b>BOILING POINT</b>	396 - 405 °F	202 - 207 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	4%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	0.35 lb/gal	43 g/l
	0.35 lb/gal	43 g/l
	Less Water and Federally Exempt Solvents	
	Emitted VOC	

## SECTION 10 — STABILITY AND REACTIVITY

**STABILITY** — Stable

**CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

## SECTION 11 — TOXICOLOGICAL INFORMATION

**CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
100-51-6	Phenylmethanol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
84852-15-3	4-Nonylphenol	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
68609-97-2	Alkyl Glycidyl Ether	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
15625-89-5	Trimethylolpropane Triacrylate	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
25085-99-8	Epoxy Polymer	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

## SECTION 12 — ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION**

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED).

Larger Containers are Regulated as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Bulk Containers may be Shipped as:

UN3066, PAINT, 8, PG III, (ERG#153)

### Canada (TDG)

UN3066, PAINT, CLASS 8, PG III, LIMITED QUANTITY, (ERG#153)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN3066, PAINT, CLASS 8, PG III, EmS F-A, S-B

### IATA/ICAO

UN3066, PAINT, 8, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.