

Gaco Western

S I N C E 1 9 5 5

Product Data Sheet:

GacoFlex 66B
October 2011
Supersedes 12/06

GACOFLEX® 66B **POLYESTER REINFORCING TAPE**

DESCRIPTION:	GacoFlex 66B parchment-like texture tape is made of fusion bonded fabric polyester fibers laid in random orientation. It exhibits a high tensile strength, good elongation and a low profile.
USAGE:	Plywood joints, concrete construction joints, concrete cracks, and joints between metal, fiberglass or insulation, and combinations of the above substrates in roof, deck and wall specifications. The 66B tape can also be used for flashing at changes of plane; however, installation into inside corners requires special care.
COLOR:	White

APPLIED PRODUCT DATA

TENSILE:	ASTM D-412-68	400 psi (2.76 MPa) Transverse 800 psi (5.52 MPa) Longitudinal
ELONGATION:	ASTM D-412-68	60%
ADHESION:	ASTM D-903-49	Same as that of Primer used.
SOLVENT SWELL:	None measurable.	
HEAT SHRINKAGE:	None after 6 months at 150°F (66°C).	

PACKAGED PRODUCT DATA

LENGTH:	100 Yards per roll (91.44 m)
THICKNESS:	5 Mils (.13mm)
STORAGE:	Store in a cool, dry place.

APPLICATION

Refer to General Instructions GW-1-2 and Details GW-5-D2.

