

# Gaco Western

S I N C E 1 9 5 5

## Product Data Sheet:

GacoFlex GacoWash

March 2014

Supersedes 10/13

### GACOFLEX® GACOWASH CONCENTRATED CLEANER

DESCRIPTION:	GacoWash is a concentrated cleaning solution for roof membranes and existing waterproof systems. It is specially formulated to remove tough dirt, pollen, mildew and fungus.
USAGE:	GacoWash is ideal for use as a cleaning solution for aged asphalt, aged EPDM and TPO/CPA, built-up, cap sheet, composite, concrete, fiberglass, metal, modified bitumen, torchdown, most existing coatings and coated polyurethane foam.
COLOR:	Clear Yellow/Amber

#### PACKAGED PRODUCT DATA

THEORETICAL COVERAGE:	400 sq. ft. per diluted gallon (9.84 m <sup>2</sup> / L) when combined 1 part GacoWash to 9 parts water. (Maximum coverage of 1 gallon GacoWash combined with 9 gallons water is 4,000 sq. ft.) Note: Amount of cleaner required is job-specific; higher concentrations may be needed for adequate cleaning.
VOC:	0
FLASH POINT:	None
STORAGE STABILITY:	One year in original unopened container.

#### APPLICATION

MIXING:	For general cleaning, combine 1 part GacoWash Concentrated Cleaner with 9 parts water. <b>Caution:</b> Never mix GacoWash with other cleaning chemicals and always avoid contact with chlorine-based cleaners as the combination of these cleaners may produce a toxic gas release.
SURFACE PREPARATION:	<b>It is extremely important to get the roof clean and dry.</b> First remove heavy deposits of dirt, leaves and other debris from the roof using broom or air broomer then inspect the entire roof surface and flashings for any open seams, tears, cuts, etc. Repair these flaws so water is not blown in under membrane during the cleaning process. Pressure wash roof with water and allow it to dry completely. Biological Control: Areas of algae, mildew or fungus on the roof membrane or the existing coating should be treated with a solution of 1 part household bleach and 3 parts water, followed by a power washer rinse using clear water.
APPLICATION:	After the roof is completely dry from initial cleaning described above, apply GacoWash with a low pressure sprayer, using a 3-4 foot (0.91-1.22 m) arc pattern. A Hudson-type agricultural sprayer, conventional pressure sprayer or airless sprayer is recommended. Allow solution to stand for 10-15 minutes, adding a light mist of water to prevent drying. While it stands, lightly agitate any heavily soiled areas with a broom or brush. Do not allow dirt to settle in low areas.  After application of cleaner, use a commercial power washer >3,000 psi (20.69 MPa) to remove debris and continue rinsing until all suds are gone. Start at the lowest point of the roof and work towards the highest point. For low-sloped roofs, work away from and then back towards roof drains. It is important to keep the surface wet until all of the GacoWash and other residue has been completely rinsed off and the surface is clean. After cleaning and rinsing the roof, ensure no dirt or debris is present. Allow surfaces to thoroughly dry to prevent blistering.

DRY TIME: Drying time depends on weather conditions such as temperature, humidity and air movement.

For specific Safety and Health information please refer to Material Safety Data Sheet.

Made in the USA

• gaco.com •

800.331.0196

