



KÖSTER Oil Cleaner

Technical guideline / Article number **9.12**
Issued: January 15, 2010

Water-based oil emulsifier for oil polluted, mineral substrates

Features

KÖSTER Oil Cleaner is a cleaner on tenside-base for cleaning oil-polluted mineral substrates.

Field of application

KÖSTER Oil Cleaner is intended for the removal of oil-, benzine- and diesel-contaminations.

Application

KÖSTER Oil Cleaner is brushed into the substrate intensively using a firm brush. After a short residence time (approx. 10 minutes), the cleaner is removed using a mop, brush or high water pressure cleaner and warm water.

We recommend to work in sections.

Packaging

10 l and 30 l canister

Storage

In originally sealed packages, the material is indefinitely storable.
Protect from frost.

Safety precautions

Wear solvent resistant protective gloves and goggles.

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.