

03 00 00 Concrete

03 01 30.51 Cleaning of Cast-In-Place Concrete

03 30 00 Cast-In-Place Concrete**09 00 00 Finishes**

09 01 60 Maintenance of Flooring

CONSOLIDECK®
HIGH PERFORMANCE CONCRETE

DAILYKlean ULTRA 15

economical daily maintenance cleaner concentrate for automatic floor scrubbersNonfood Compounds
Program Listed A4
Registration #148963

OVERVIEW

Consolideck® DailyKlean ULTRA 15 is a concentrated maintenance cleaner for concrete floors, including floors hardened and densified with lithium silicate products. It's pre-measured for 15 gallon auto-scrubber tanks. Just add a 4 ounce pax of DailyKlean Ultra 15 to a 15 gallon auto scrubber tank of fresh water, and you're ready to clean.

This specialized blend of degreasers and detergents removes most common soiling found on concrete floors daily. It is ideal for concrete floors everywhere, from warehouses and manufacturing plants to schools, stores, hospitals, restaurants and more.

Though DailyKlean ULTRA 15 is specifically made for floors hardened and densified with Consolideck® LS® lithium silicate hardener/densifier, it's perfect for almost any concrete floor.

Used as part of a comprehensive maintenance program, DailyKlean ULTRA 15 helps ensure the highest appearance and performance standards for all indoor concrete flatwork.

SPECIFICATIONS

For all PROSOCO product specifications visit www.prosoco.com.

ADVANTAGES

- Maintains concrete floor shine.
- Removes most common soiling.
- Flexible dilution for both surface and deep cleaning.
- Readily biodegradable; low toxicity.
- Contains U.S. EPA DfE (Design for the Environment) conformant CleanGredients® listed surfactants.
- Concentrated for economy of storage and transport.
- No rinsing needed for routine surface cleaning of floors.
- Ideal for auto scrubbers.

Limitations

- May not remove some embedded stains.
- Does not contain lithium silicate. Has no hardening/densifying effect.

REGULATORY COMPLIANCE

Consolideck® DailyKlean ULTRA 15 is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	Clear orange liquid fresh, clean odor
SPECIFIC GRAVITY	0.998
pH	7.84
WT/GAL	8.15 pounds
ACTIVE CONTENT	Not applicable
TOTAL SOLIDS	Not applicable
VOC CONTENT	<1%
FLASH POINT	>200°F (>93°C) ASTM D 3278
FREEZE POINT	31°F (-0.5°C)
SHELF LIFE	2 years in tightly-sealed, unopened container

DAILY Klean ULTRA 15

PREPARATION

Sweep or vacuum to remove loose materials from the surface to be cleaned.

Pre-clean oil spots or other deep stains with the appropriate Consolideck® product. For recommendations, call Customer Care toll-free at 800-255-4255.

Surface and Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C). Do not apply at temperatures below 40°F (4°C).

Equipment

This product is specially concentrated for use with an automatic floor scrubber.

Use soft brushes/soft pads. Never use aggressive brushes or pads on polished concrete.

Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 45-100°F (7-38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use, read "Preparation" and "Safety Information."

ALWAYS TEST for suitability, dilution rates and desired results before overall application. Test using the following application instructions. Let surface dry thoroughly before inspection.

Dilution

Dilute one 4 oz PAX per 15 gallons of fresh water.

ALWAYS TEST

ALWAYS TEST a small area of each surface to confirm suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application.

Application Instructions

1. Apply with an automatic scrubber.
2. For routine cleaning, rinsing the concrete floor is not necessary. Vacuum up spent cleaner and dissolved contaminants with auto scrubber.
For deep cleaning, or for cleaning in food-processing areas, rinse well with fresh water. Do not let puddles or concentrated cleaner dry on the floor. Vacuum up rinse water with automatic scrubber.
3. Buff the cleaned floor with a white pad to increase the shine.

Cleanup

Clean tools and equipment using fresh water.

DAILYKlean ULTRA 15

SAFETY INFORMATION

Consolideck® DailyKlean ULTRA 15 is a commercial strength concentrated cleaner and may cause irritation. Field-diluted solution may cause eye and skin irritation. Use appropriate safety equipment and job site controls during application. Read full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: Do not induce vomiting. Get immediate medical assistance.

Eye Contact: Rinse thoroughly for 15 minutes. Get medical assistance.

Skin Contact: Rinse thoroughly. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Get medical attention as necessary.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com for the name of the Consolideck® representative in your area.

BEST PRACTICES

For spot cleaning heavily soiled areas, begin testing DailyKlean ULTRA 15 at a dilution of 2 ounces of cleaner to 5 gallons of fresh water.

For regular maintenance cleaning, always use one 4 ounce PAX of DailyKlean ULTRA 15 with a full 15 gallon auto scrubber tank of fresh water.

Do not let spent cleaner and dissolved contaminants dry on the floor.

To remove deeply embedded oil and grease stains, test Consolideck® Oil & Grease Stain Remover.

Use soft brushes/soft pads with auto scrubbers. Never use aggressive brushes or pads on polished concrete.

Use DailyKlean ULTRA 15 as part of a comprehensive maintenance program that includes deep cleaning with Consolideck® LSKlean ULTRA 15 at least once a week.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free at 800-255-4255.

DAILY Klean ULTRA 15

THIS PAGE INTENTIONALLY BLANK