

SAFETY DATA SHEET

PROSOCO, Inc.



Issue Date 11-Nov-2014

Revision Date 11-Nov-2014

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Consolideck® SingleStep®

Other means of identification

Product Code 46031
UN/ID No UN1866

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address
 PROSOCO, Inc.
 3741 Greenway Circle
 Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday 785-865-4200
NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Flammable liquids	Category 3

Label elements

Emergency Overview

<p>Danger</p> <p>Hazard statements Harmful if inhaled Causes skin irritation May cause genetic defects May cause cancer May damage fertility or the unborn child Flammable liquid and vapor</p>

**Appearance** clear**Physical state** Liquid**Odor** Aromatic**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/./? /equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Xylene	1330-20-7	40 - 70	*
Ethylbenzene	100-41-4	10 - 30	*
Solvent Naptha (petroleum) light aromatic	64742-95-6	5 - 10	*
Triethoxyoctysilane	2943-75-1	1 - 5	*
1,2,4-trimethylbenzene	95-63-6	1 - 5	*
dibutyl phthalate	84-74-2	1 - 5	*

Toluene	108-88-3	0.1 - 1	*
---------	----------	---------	---

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. Immediate medical attention is not required.
Inhalation	Move to fresh air in case of accidental inhalation of vapors or decomposition products. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is required.
Ingestion	Call a physician or poison control center immediately. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Irritating to eyes and skin. Harmful if inhaled.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO₂). Foam. Water spray (fog).

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Ground and bond containers when transferring material. Use only non-sparking tools.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents. Acids. Halogens.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
1,2,4-trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³

dibutyl phthalate 84-74-2	TWA: 5 mg/m ³	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 4000 mg/m ³ TWA: 5 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Aromatic
Appearance	clear	Odor threshold	No information available
Color	colorless		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not Applicable	Not Applicable	
Melting point/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash point	41 °C / 105 °F	Tag Closed Cup	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
Upper flammability limits	No information available		
Lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	0.92 @ 20C		
Water solubility	Insoluble in water		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		

Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Halogens.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Avoid contact with skin, eyes and inhalation of vapors Harmful by inhalation Irritating to eyes, skin and respiratory tract
Inhalation	Harmful by inhalation.
Eye contact	May cause irritation.
Skin Contact	Causes skin irritation.
Ingestion	Do not taste or swallow. Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Solvent Naptha (petroleum) light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h
Triethoxyoctylsilane 2943-75-1	= 10060 µL/kg (Rat)	= 5910 µL/kg (Rabbit)	-
1,2,4-trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
dibutyl phthalate 84-74-2	= 6300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 15.68 mg/L (Rat) 4 h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit) = 12124 mg/kg (Rat)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h

Information on toxicological effects

Symptoms Irritating to eyes, respiratory system and skin. Harmful if inhaled.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X
Toluene 108-88-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic toxicity Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system.
Target Organ Effects blood, central nervous system, Eyes, Gastrointestinal tract (GI), Respiratory system, Skin.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4108 mg/kg
ATEmix (dermal) 2114 mg/kg mg/l
ATEmix (inhalation-dust/mist) 1.6 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea

Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	-	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Solvent Naptha (petroleum) light aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	-	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	-	6.14: 48 h Daphnia magna mg/L EC50
dibutyl phthalate 84-74-2	1.2: 72 h Desmodesmus subspicatus mg/L EC50 0.4: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	0.71 - 1.2: 96 h Pimephales promelas mg/L LC50 flow-through 0.31 - 5.45: 96 h Pimephales promelas mg/L LC50 static 1.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.24 - 5.3: 96 h Oncorhynchus mykiss mg/L LC50 static 1.38 - 1.74: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.42 - 1.28: 96 h Lepomis macrochirus mg/L LC50 static	-	2.99: 48 h Daphnia magna mg/L EC50 Static 3.4: 48 h Daphnia magna mg/L EC50

Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	-	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
---------------------	---	--	---	--

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
1,2,4-trimethylbenzene 95-63-6	3.63
dibutyl phthalate 84-74-2	5.38
Toluene 108-88-3	2.65

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U069

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
dibutyl phthalate 84-74-2	U069	-	-	U069

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated (If shipped in NON BULK packaging by ground transport)
UN/ID No UN1866
Proper shipping name Resin Solution
Hazard Class 3
Packing Group III

IATA
UN/ID No UN1866
Proper shipping name Resin Solution
Hazard Class 3
Packing Group III

IMDG
UN/ID No UN1866
Proper shipping name Resin Solution
Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	40 - 70	1.0
Ethylbenzene - 100-41-4	100-41-4	10 - 30	0.1
1,2,4-trimethylbenzene - 95-63-6	95-63-6	1 - 5	1.0
dibutyl phthalate - 84-74-2	84-74-2	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

Xylene 1330-20-7	100 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	X	X	X
dibutyl phthalate 84-74-2	10 lb	X	X	X
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
dibutyl phthalate 84-74-2	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
dibutyl phthalate - 84-74-2	Developmental Female Reproductive Male Reproductive
Toluene - 108-88-3	Developmental Female Reproductive
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X
1,2,4-trimethylbenzene 95-63-6	X	X	X
dibutyl phthalate 84-74-2	X	X	X
Toluene 108-88-3	X	X	X

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2*	Flammability 2	Physical hazards 0	Personal protection X

Prepared By Regulatory Department
Issue Date 11-Nov-2014
Revision Date 11-Nov-2014
Revision Note
No information available

Disclaimer

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet