

32 14 00 Unit Paving

32 14 13 Precast Concrete Unit Paving

32 14 16 Brick Unit Paving

32 14 40 Stone Paving

PRODUCT DATA SHEET**PROSOCO**
SINCE 1939**PAVER KARE®****Deep Sheen***high-gloss protective treatment for pavers***OVERVIEW**

Glossy, slip-resistant Paver Kare® Deep Sheen is the perfect treatment for pavers, inside or out. This durable protective treatment weather- and stain-proofs new or newly cleaned pavers, giving them a premium, vibrant gloss and shine. Deep Sheen adds luster and brings out the real beauty of clay and stone pavers. Highly tested Deep Sheen will not “yellow,” blush or dull-out.

Deep Sheen’s chemical-resistant, glossy finish guards pavers against any number of etching and staining acidic and alkaline contaminants, including food, drinks, cleaning chemicals and more. Fast-drying and non-yellowing Deep Sheen is ideal for paver installations of any size, new or old.

SPECIFICATIONS

For all PROSOCO product specifications visit www.prosoco.com.

ADVANTAGES

- Non-yellowing. Surface stays clear.
- Slip-resistant.
- Passed 300 hours QUV resistance (ASTM G 154).
- Reduces clean up effort and resists construction stains.
- Protects against alkali, oil, cleaners and common chemicals.
- Prevents efflorescence, dusting and spalling.
- Quick drying.
- Re-coatable, excellent base for most adhesives.

Limitations

- Will not bond to cementitious adhesives. Test for bondability to new products.
- Not for use around pools or fountains.
- Not designed for application to asphaltic or painted surfaces. Always test.
- Will not compensate for structural or surface defects.
- Not recommended for below-grade application.
- Not suitable for sale in states and districts with more restrictive AIM VOC regulations.

REGULATORY COMPLIANCE**VOC Compliance**

Paver Kare® Deep Sheen is compliant with the following national, state and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts
- South Coast Air Quality Management District
- Maricopa County, AZ
- Northeast Ozone Transport Commission

Deep Sheen is manufactured and marketed in compliance with US EPA AIM VOC regulations (40 CFR 59.403).

TYPICAL TECHNICAL DATA

FORM	clear liquid
SPECIFIC GRAVITY	0.770
pH	Not applicable
WT/GAL	7.4 lbs
ACTIVE CONTENT	30% ±2%
TOTAL SOLIDS	30% ±2%
VOC CONTENT	>600 g/L
FLASH POINT	>100°F (>38°C)
FREEZE POINT	-8°F (-22°C)
SHELF LIFE	1 year in tightly sealed, unopened container

Deep Sheen

PREPARATION

Protect people, vehicles, property, plants, windows and all non masonry surfaces from product, splash, residue, fumes and wind drift. Protect and/or divert foot and auto traffic. Pavers must be clean, dry and in good repair before application.

Ensure fresh air entry and cross ventilation during application and drying. Extinguish all flames, pilot lights and other potential sources of ignition during use and until all vapors are gone. Avoid exposing passersby and building occupants to product, fumes and mist.

Surface and Air Temperatures

Do not apply when temperatures are less than 40°F (4°C).

Equipment

Apply by brush, long-nap roller, lamb's wool applicator or low pressure spray equipment. Fit spray equipment with steel or brass fittings and gaskets suitable for solvent solutions. Brushes and rollers should be nylon or other synthetic material resistant to solvent solutions. Avoid atomization of the material.

Storage and Handling

Store in a cool, dry place away from potential ignition sources. Keep container tightly sealed when not dispensing. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use, read "Preparation" and "Safety Information."

ALWAYS TEST each surface and type of stain for suitability, dilution rates and desired results before overall application. Use the following application instructions. Let surface dry thoroughly before inspection and approval.

Dilution

Apply as packaged. Do not dilute or alter. Mix well before use.

Coverage Rates

Coverage varies based upon paver porosity and texture. Always test.

Concrete Pavers

- 40–60 square feet per gallon
- 4–6 square meters per gallon

Clay Pavers

- 75–100 square feet per gallon
- 7–9 square meters per gallon

Stone Pavers

- 200–400 square feet per gallon
- 19–37 square meters per gallon

ALWAYS TEST

ALWAYS TEST a small area of each surface to confirm suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application.

Application Instructions

Cover surface uniformly, creating a continuous film. Two coats may be needed for porous concrete pavers. Add the second coat four hours after the first. Two thin coats are always preferred over one heavy coat.

Drying Time

At 80°F (27°C), treated surfaces dry:

To touch	25 minutes
Light foot traffic.....	4 hours
Normal traffic.....	Overnight
Maximum hardness.....	7 days

Cleanup

Clean tools and equipment with Defacer Eraser® Graffiti Wipe, mineral spirits or similar solvent.

Deep Sheen

SAFETY INFORMATION

Paver Kare® Deep Sheen is a solvent-carried product and may cause symptoms typical with organic solvent exposures. This is a combustible material. Use appropriate ventilation, safety equipment and job site controls during application and handling. Read the full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: If swallowed, call a physician immediately. ASPIRATION HAZARD. Do not induce vomiting or give anything by mouth. Only induce vomiting at the instructions of a physician. If vomiting occurs, keep head below waist to prevent entry of liquid into lungs.

Eye Contact: Rinse eyes thoroughly for 15 minutes. Get medical assistance if irritation persists.

Skin Contact: Rinse thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if irritation develops.

Inhalation: Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get immediate medical attention.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation

encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com for the name of the Paver Kare® representative in your area.

BEST PRACTICES

Do not use around pools, fountains or other water features.

Paver surfaces should be clean, dry and absorbent before application.

Clean soiled paver surfaces with Sure Clean® Light Duty Concrete Cleaner before application.

Preferred method of application is low-pressure spray equipment. Use a fan-type spray tip and adjust pressure to avoid atomization of the material.

Apply evenly. Be careful not to over apply.

Two coats may be needed for porous concrete pavers. Two thin coats are always preferable to one heavy coat.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free at 800-255-4255.

PAVER KARE®

Deep Sheen

PRODUCT DATA SHEET

PROSOCO
SINCE 1939

THIS PAGE INTENTIONALLY BLANK