

**1. Product and company identification**

Product name	Sikafloor® NA PurCem® Part A
Supplier	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071
Telephone	(201) 933-8800
Telefax	(201) 804-1076
Emergency telephone	CHEMTREC: 800-424-9300
e-mail address of person responsible for this SDS	INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Manufacturer	Sika Corporation, Operations 201 Polito Avenue Lyndhurst, NJ 07071
Telephone	www.sikausa.com (201) 933 - 8800

2. Hazards identification

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Potential Health Effects

Inhalation	May cause respiratory tract irritation. Harmful if inhaled in high concentrations
Skin	May cause skin irritation.
Eyes	May cause eye irritation.
Ingestion	May cause gastrointestinal disturbance.
Warning	Causes central nervous system depression Possible cancer hazard. Contains material which may cause cancer based on animal data.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

<u>Component</u>	<u>CAS Number</u>
Castor oil	8001-79-4
butane-1,4-diol	110-63-4
titanium dioxide	13463-67-7
Distillates (petroleum), hydrotreated middle	64742-46-7
Carbon black	1333-86-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



4. First aid measures

First aid procedures

Inhalation	If inhaled, remove to fresh air. If breathing is difficult, trained personnel should give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately if irritation develops and persists.
Eye contact	If easy to do, remove contact lens, if worn. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	If swallowed, contact a poison control center or physician immediately. Do NOT induce vomiting unless directed to do so by medical personnel Never give anything by mouth to an unconscious person.

Notes to physician

Treatment	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
-----------	--

5. Fire-fighting measures

Fire fighting

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	none
Further information	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training.

Protective equipment and precautions for firefighters

Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
---	--

6. Accidental release measures

Personal precautions	Use personal protective equipment.
----------------------	------------------------------------



	<p>Ensure adequate ventilation. Evacuate personnel to safe areas. No action shall be taken involving any personal risk without suitable training. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Material can create slippery conditions.</p>
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for containment and cleaning up	<p>Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Large spills should be collected mechanically (remove by pumping) for disposal.</p>

7. Handling and storage

Handling	<p>For personal protection see section 8. Avoid inhalation, ingestion and contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area.</p>
Storage	<p>Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. To maintain product quality, do not store in heat or direct sunlight. Store in accordance with local regulations.</p>

8. Exposure controls/personal protection

<u>Exposure limit(s)</u>					
<u>Component</u>	<u>CAS Number</u>	<u>Content %</u>	<u>Basis *</u>	<u>Value</u>	<u>Exposure limit(s) / Form of exposure</u>
titanium dioxide	13463-67-7	2.5 - 5	ACGIH	TWA	10 mg/m3
		2.5 - 5	OSHA P0	TWA	10 mg/m3 Total
		2.5 - 5	OSHA Z-1	TWA	15 mg/m3 total dust
Carbon black	1333-86-4	0 - 1	ACGIH	TWA	3.5 mg/m3
		0 - 1	OSHA Z-1	TWA	3.5 mg/m3
		0 - 1	OSHA P0	TWA	3.5 mg/m3

*** Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminant (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Eye protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.

9. Physical and chemical properties**Appearance**

Form liquid

Color various

Safety data

Flash point Note: not applicable

Density 1.1 - 1.25 g/cm³

Viscosity, kinematic > 20.5 mm²/s

Volatile organic compounds
(VOC) content < 5 g/l (A+B+C Combined)



10. Stability and reactivity

Stability	Stable under normal conditions. No dangerous reaction known under conditions of normal use.
Conditions to avoid	not applicable
Materials to avoid	not applicable
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Acute oral toxicity	Component: 1,4-butanediol LD50 Oral rat Dose: 1,500 mg/kg
Acute dermal toxicity	Component: 1,4-butanediol LD50 Dermal rat Dose: > 2,000 mg/kg
Acute inhalation toxicity	Component: 1,4-butanediol LC50 rat Exposure time: 4 h Dose: 5.1 mg/l
Chronic Exposure	Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Carcinogenicity

IARC	Group 2B: Possibly carcinogenic to humans titanium dioxide 13463-67-7 Carbon black 1333-86-4
OSHA	not applicable
NTP	not applicable
ACGIH	not applicable

12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------	--

13. Disposal considerations

Waste disposal methods	Disposal of this product, solutions and any by-products should at all
------------------------	---



Packaging

times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT
Not dangerous goods
IATA
Not dangerous goods
IMDG
Not dangerous goods

15. Regulatory information

Federal Regulations

TSCA Status On TSCA Inventory
SARA 311/312 Hazards Acute Health Hazard
Chronic Health Hazard

EPCRA - Emergency Planning Community Right - To - Know

SARA 302 Ingredients not applicable
SARA 313 Ingredients not applicable

Clean Air Act

Ozone-Depletion Potential This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

State Regulations

California Prop. 65 Ingredients WARNING! This product contains a chemical known in the State of California to cause cancer.


16. Other information



HMIS Classification

Health	*	1
Flammability		0
Physical Hazard		0
Personal Protection		B

NFPA Classification



Caution: HMIS® ratings and NFPA ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® and NFPA ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® and NFPA ratings are to be used with a fully implemented HMIS® and NFPA program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). NFPA or the National Fire Protection Association is a private non-profit organization and an authoritative source of technical background, data, and consumer advice on fire protection, problems and prevention. Please note HMIS® attempts to convey full health warning information to all employees while NFPA is meant primarily for fire fighters and other emergency responders.

Notes to Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

**1. Product and company identification**

Product name	Sikafloor® NA PurCem® Part B
Supplier	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071
Telephone	(201) 933-8800
Telefax	(201) 804-1076
Emergency telephone	CHEMTREC: 800-424-9300
e-mail address of person responsible for this SDS	INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Manufacturer	Sika Corporation, Operations 201 Polito Avenue Lyndhurst, NJ 07071
Telephone	www.sikausa.com (201) 933 - 8800

2. Hazards identification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Potential Health Effects

Inhalation	Causes respiratory tract irritation. Harmful if inhaled. May cause allergic respiratory reaction.
Skin	May cause allergic skin reaction. Causes skin irritation.
Eyes	Causes eye irritation.
Ingestion	Harmful if swallowed.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

<u>Component</u>	<u>CAS Number</u>
methylenediphenyl diisocyanate	26447-40-5
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures**First aid procedures**



Inhalation	If inhaled, remove to fresh air. If breathing is difficult, trained personnel should give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Skin contact	In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately if irritation develops and persists.
Eye contact	If easy to do, remove contact lens, if worn. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	If swallowed, contact a poison control center or physician immediately. Do NOT induce vomiting unless directed to do so by medical personnel Never give anything by mouth to an unconscious person. Get medical attention immediately.

Notes to physician

Treatment	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
-----------	--

5. Fire-fighting measures**Fire fighting**

Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	none
Further information	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training.

Protective equipment and precautions for firefighters

Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
---	--

6. Accidental release measures

Personal precautions	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. No action shall be taken involving any personal risk without suitable
----------------------	--



	training. Keep people away from and upwind of spill/leak. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Material can create slippery conditions.
Environmental precautions	Local authorities should be advised if significant spillages cannot be contained. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for containment and cleaning up	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Large spills should be collected mechanically (remove by pumping) for disposal.

7. Handling and storage

Handling	For personal protection see section 8. Avoid inhalation, ingestion and contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. To maintain product quality, do not store in heat or direct sunlight. Store in accordance with local regulations.

8. Exposure controls/personal protection

Exposure limit(s)

Contains no substances with occupational exposure limit values.

* **Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminant (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
----------------------	--

Personal protective equipment

Eye protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



Skin and body protection	Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hygiene measures	Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

9. Physical and chemical properties

Appearance

Physical state	liquid
Color	amber
Odor	musty

Safety data

Flash point	424 °F (218 °C)
Ignition temperature	464 °F (240 °C)
Density	1.2 g/cm ³
Viscosity, kinematic	> 20.5 mm ² /s
Volatile organic compounds (VOC) content	< 5 g/l (A+B+C Combined)

10. Stability and reactivity

Stability	Stable under normal conditions.
Conditions to avoid	not applicable
Materials to avoid	not applicable
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information



Chronic Exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

not applicable

IARC

not applicable

OSHA

not applicable

NTP

not applicable

ACGIH

not applicable

12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

13. Disposal considerations

Waste disposal methods

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

15. Regulatory information

Federal Regulations

TSCA Status

On TSCA Inventory

SARA 311/312 Hazards

Acute Health Hazard

EPCRA - Emergency Planning Community Right - To - Know

SARA 302 Ingredients

not applicable

SARA 313 Ingredients

Diphenylmethanediisocyanate, isomers and homologues

9016-87-9

40 %

Clean Air Act



Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

State Regulations

**California Prop. 65
Ingredients**


This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. Other information

HMIS Classification

Health	*	2
Flammability		1
Physical Hazard		0
Personal Protection		G

NFPA Classification



Caution: HMIS® ratings and NFPA ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® and NFPA ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® and NFPA ratings are to be used with a fully implemented HMIS® and NFPA program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). NFPA or the National Fire Protection Association is a private non-profit organization and an authoritative source of technical background, data, and consumer advice on fire protection, problems and prevention. Please note HMIS® attempts to convey full health warning information to all employees while NFPA is meant primarily for fire fighters and other emergency responders.

Notes to Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.



SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.



1. Identification

Product name : Sikafloor®-19 NA PurCem® Part C

Supplier : Sika Corporation

Address : 201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887
ehs@sika-corp.com



Recommended use of the chemical and restrictions on use : For further information, refer to the product technical data sheet.

2. Hazards identification

GHS Classification

Skin irritation, Category 2 H315: Causes skin irritation.
Serious eye damage, Category 1 H318: Causes serious eye damage.
Carcinogenicity, Category 1A H350: May cause cancer.

GHS Label element

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H350 May cause cancer.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
P280 Wear protective gloves.
P281 Use personal protective equipment as required.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water



for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P310 Immediately call a POISON CENTER or doctor/physician.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Quartz (SiO ₂)	14808-60-7	>= 50 - <= 100 %
Portland cement	65997-15-1	>= 10 - < 20 %
Calcium hydroxide	1305-62-0	>= 2 - < 5 %
Quartz (SiO ₂) <5µm	14808-60-7	>= 0 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Induce vomiting immediately and call a physician.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.



	Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
	irritant effects carcinogenic effects
Protection of first-aiders	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
Notes to physician	: Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the
-------------------------	---



application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Prevent unauthorized access.
Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

Materials to avoid : no data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO ₂)	14808-60-7	ACGIH	TWA	0.025 mg/m ³ Respirable fraction
		OSHA Z-3	TWA	30 mg/m ³ / %SiO ₂ +2 total dust
		OSHA Z-3	TWA	10 mg/m ³ / %SiO ₂ +2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO ₂ +5 respirable
		OSHA P0	TWA	0.1 mg/m ³ Respirable fraction
Portland cement	65997-15-1	ACGIH	TWA	1 mg/m ³ Respirable fraction
		OSHA P0	TWA	10 mg/m ³ Total
		OSHA P0	TWA	5 mg/m ³ Respirable fraction
		OSHA Z-1	TWA	15 mg/m ³ total dust
		OSHA Z-1	TWA	5 mg/m ³ respirable fraction
		OSHA Z-3	TWA	50 Million particles per cubic foot



				Dust
Calcium hydroxide	1305-62-0	ACGIH	TWA	5 mg/m3
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	5 mg/m3
Quartz (SiO ₂) <5µm	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO ₂ +2 total dust
		OSHA Z-3	TWA	10 mg/m3 / %SiO ₂ +2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO ₂ +5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

****Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.



The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection	
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling. Avoid breathing dust.

9. Physical and chemical properties

Appearance	: powder
Color	: gray
Odor	: odorless
Odor Threshold	: no data available
Flash point	: Note: not applicable
Ignition temperature	: no data available
Decomposition temperature	: no data available
Lower explosion limit (Vol%)	: no data available
Upper explosion limit (Vol%)	: no data available
Flammability (solid, gas)	: no data available
Oxidizing properties	: no data available
Autoignition temperature	: no data available
pH	: Note: not applicable



Melting point/range / Freezing point	:	no data available
Boiling point/boiling range	:	no data available
Vapor pressure	:	no data available
Density	:	ca.2.8 g/cm ³ at 73 °F (23 °C)
Water solubility	:	Note: insoluble
Partition coefficient: n-octanol/water	:	no data available
Viscosity, dynamic	:	no data available
Viscosity, kinematic	:	Note: not applicable
Relative vapor density	:	no data available
Evaporation rate	:	no data available
Burning rate	:	no data available
Volatile organic compounds (VOC) content	:	< 5 g/l NA PurCem (AB)+ 19 NA PurCem (C) Combined

10. Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	no data available
Incompatible materials	:	no data available

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity	:	no data available
Acute inhalation toxicity	:	no data available
Acute dermal toxicity	:	no data available

Skin corrosion/irritation



Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

Causes serious eye damage.

Respiratory or skin sensitization

Product

no data available

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : May cause cancer.

IARC

Group 1: Carcinogenic to humans

Quartz (SiO₂) 14808-60-7

Quartz (SiO₂) <5µm 14808-60-7

NTP

Known to be human carcinogen

Quartz (SiO₂) 14808-60-7

Quartz (SiO₂) <5µm 14808-60-7

Reproductive Toxicity/Fertility

Product

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Assessment: no data available

STOT-repeated exposure

Prolonged exposure can cause silicosis.

Product

Assessment: no data available

Aspiration toxicity



Product

no data available

12. Ecological information

Other information : Do not empty into drains; dispose of this material and its container in a safe way.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity



This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 WARNING! This product contains a chemical known in the State of California to cause cancer.
WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

16. Other information

HMIS Classification

Health	*	3
Flammability		0
Physical Hazard		0
Personal Protection		X

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader



The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/17/2014

Material number: 461979