Revision Date 07/12/2013 Print Date 07/12/2013

1. Product and company identification

Product name Sikafloor® NA PurCem® Part A

Supplier Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

Telephone (201) 933-8800 Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300 e-mail address of person INTERNATIONAL: 703-527-3887

responsible for this SDS ehs@sika-corp.com

Manufacturer Sika Corporation, Operations

201 Polito Avenue Lyndhurst, NJ 07071 www.sikausa.com

Telephone (201) 933 - 8800

2. Hazards identification

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Potential Health Effects

Inhalation May cause respiratory tract irritation.

Harmful if inhaled in high concentrations

Skin May cause skin irritation.

Eyes May cause eye irritation.

Ingestion May cause gastrointestinal disturbance.

Warning Causes central nervous system depression

Possible cancer hazard. Contains material which may cause cancer

based on animal data.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Component	CAS Number
Castor oil	8001-79-4
butane-1,4-diol	110-63-4
titanium dioxide	13463-67-7
Distillates (petroleum), hydrotreated middle	64742-46-7
Carbon black	1333-86-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Revision Date 07/12/2013 Print Date 07/12/2013

4. First aid measures

First aid procedures

Inhalation If inhaled, remove to fresh air.

If breathing is difficult, trained personnel should give oxygen.

If not breathing, give artificial respiration.

Get medical attention.

Skin contact In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Wash clothing before reuse.

Get medical attention immediately if irritation develops and persists.

Eye contact If easy to do, remove contact lens, if worn.

In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes. Get medical attention.

Ingestion If swallowed, contact a poison control center or physician

immediately.

Do NOT induce vomiting unless directed to do so by medical

personnel

Never give anything by mouth to an unconscious person.

Notes to physician

Treatment No specific treatment. Treat symptomatically. Contact poison

treatment specialist immediately if large quantities have been

ingested or inhaled.

5. Fire-fighting measures

Fire fighting

circumstances and the surrounding environment.

Unsuitable extinguishing media none

Further information Collect contaminated fire extinguishing water separately. This must

not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk without suitable training.

Protective equipment and precautions for firefighters

Special protective equipment for

firefighters

Firefighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece

operated in positive pressure mode.

6. Accidental release measures

Revision Date 07/12/2013 Print Date 07/12/2013

Ensure adequate ventilation.

Evacuate personnel to safe areas.

No action shall be taken involving any personal risk without suitable

training

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Material can create slippery conditions.

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers.

Methods for containment and

cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a

container for disposal according to local / national regulations (see

section 13).

Large spills should be collected mechanically (remove by pumping)

for disposal.

7. Handling and storage

Handling For personal protection see section 8.

Avoid inhalation, ingestion and contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the application

area

Storage Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep in properly labeled containers.

To maintain product quality, do not store in heat or direct sunlight.

Store in accordance with local regulations.

8. Exposure controls/personal protection

Exposure limit(s)

Component	CAS Number	Content %	Basis *	<u>Value</u>	Exposure limit(s) / Form of exposure
titanium dioxide	13463-67-7	2.5 - 5	ACGIH	TWA	10 mg/m3
		2.5 - 5	OSHA P0	TWA	10 mg/m3 Total
		2.5 - 5	OSHA Z-1	TWA	15 mg/m3 total dust
Carbon black	1333-86-4	0 - 1	ACGIH	TWA	3.5 mg/m3
		0 - 1	OSHA Z-1	TWA	3.5 mg/m3
		0 - 1	OSHA P0	TWA	3.5 mg/m3

Revision Date 07/12/2013 Print Date 07/12/2013

* Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure below any recommended or statutory limits.

Personal protective equipment

Eye protection Safety eyewear complying with an approved standard should be

used when a risk assessment indicates this is necessary.

Hand protection Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

an approved standard if a risk assessment indicates this is

necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment before

entering eating areas.

9. Physical and chemical properties

Appearance

Form liquid
Color various

Safety data

Flash point Note: not applicable

Density 1.1 - 1.25 g/cm3

Viscosity, kinematic > 20.5 mm2/s

Volatile organic compounds

(VOC) content

< 5 g/l (A+B+C Combined)

Revision Date 07/12/2013 Print Date 07/12/2013

10. Stability and reactivity

Stability Stable under normal conditions.

No dangerous reaction known under conditions of normal use.

Conditions to avoid not applicable

Materials to avoid not applicable

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

11. Toxicological information

Acute oral toxicity Component: 1,4-butanediol

LD50 Oral rat Dose: 1,500 mg/kg

Acute dermal toxicity Component: 1,4-butanediol

LD50 Dermal rat Dose: > 2,000 mg/kg

Acute inhalation toxicity Component: 1,4-butanediol

LC50 rat

Exposure time: 4 h Dose: 5.1 mg/l

Chronic Exposure Reports have associated repeated and prolonged exposure to some

of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans

titanium dioxide 13463-67-7

Carbon black 1333-86-4

OSHA not applicable
NTP not applicable
ACGIH not applicable

12. Ecological information

Other information Do not empty into drains; dispose of this material and its container

in a safe way.

Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers.

13. Disposal considerations

Waste disposal methods Disposal of this product, solutions and any by-products should at all

Material Safety Data Sheet

Sikafloor® NA PurCem® Part A

times comply with the requirements of environmental protection and

Print Date 07/12/2013

waste disposal legislation and any regional local authority

requirements.

Packaging Empty containers should be taken to an approved waste handling

site for recycling or disposal.

14. Transport information

Revision Date 07/12/2013

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

15. Regulatory information

Federal Regulations

TSCA Status SARA 311/312 Hazards On TSCA Inventory Acute Health Hazard Chronic Health Hazard

EPCRA - Emergency Planning Community Right - To - Know

SARA 302 Ingredients not applicable SARA 313 Ingredients not applicable

Clean Air Act

Ozone-Depletion Potential This product neither contains, nor was manufactured with a Class I or

Class II ODS as defined by the U.S. Clean Air Act Section 602 (40

CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

State Regulations

California Prop. 65 Ingredients

WARNING! This product contains a chemical known in the State of

California to cause cancer.

16. Other information


Revision Date 07/12/2013

Print Date 07/12/2013

HMIS Classification



NFPA Classification



Caution: HMIS® ratings and NFPA ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® and NFPA ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® and NFPA ratings are to be used with a fully implemented HMIS® and NFPA program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). NFPA or the National Fire Protection Association is a private non-profit organization and an authoritative source of technical background, data, and consumer advice on fire protection, problems and prevention. Please note HMIS® attempts to convey full health warning information to all employees while NFPA is meant primarily for fire fighters and other emergency responders.

Notes to Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/17/2014 Print Date 03/17/2014

1. Identification

Product name Sikafloor® NA PurCem® Part B

Sika Corporation Supplier

Address 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on

For further information, refer to the product technical data

sheet.

2. Hazards identification

use

GHS Classification

Acute toxicity, Category 4 (Inhalation) H332: Harmful if inhaled. Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2A H319: Causes serious eye irritation.

Respiratory sensitization, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H317: May cause an allergic skin reaction. Skin sensitization, Category 1 Specific target organ systemic toxicity -H335: May cause respiratory irritation.

single exposure, Category 3, Respiratory

Specific target organ systemic toxicity repeated exposure, Category 2

(Inhalation)

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

GHS Label element

Hazard pictograms





Signal Word Danger

Hazard Statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Revision Date 03/17/2014 Print Date 03/17/2014

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Precautionary Statements

: Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P285 In case of inadequate ventilation wear respiratory

protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
methylenediphenyl diisocyanate	26447-40-5	>= 50 - <= 100 %
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 25 - < 50 %
homologues		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Revision Date 03/17/2014 Print Date 03/17/2014

4. First aid measures

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

: Clean mouth with water and drink afterwards plenty of water. If swallowed

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and delayed

irritant effects sensitizing effects

Asthmatic appearance

Cough

Respiratory disorder Allergic reactions **Excessive lachrymation**

Erythema Headache **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Protection of first-aiders Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Revision Date 03/17/2014 Print Date 03/17/2014

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : no data available

8. Exposure controls/personal protection

Contains no substances with occupational exposure limit values.

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any

recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

Print Date 03/17/2014

breathing apparatus must be used.

Hand protection

Revision Date 03/17/2014

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

9. Physical and chemical properties

Appearance : liquid
Color : amber

Odor : musty

Odor Threshold : no data available

Flash point : 424 °F (218 °C)

Ignition temperature : not applicable

Decomposition temperature : no data available

Lower explosion limit (Vol%) : no data available

Upper explosion limit (Vol%) : no data available

Flammability (solid, gas) : no data available

Oxidizing properties : no data available

Autoignition temperature : no data available

I a

Sikafloor® NA PurCem® Part B

Revision Date 03/17/2014 Print Date 03/17/2014

pH : no data available

Melting point/range /

Freezing point

: no data available

Boiling point/boiling range : no data available

Vapor pressure : no data available

Density : 1.2 g/cm3

Water solubility : Note: soluble

Partition coefficient: n-

no data available

octanol/water Viscosity, dynamic

: no data available

Viscosity, kinematic : > 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : no data available

Evaporation rate : no data available

Burning rate : no data available

Volatile organic compounds

(VOC) content

: < 5 g/l NA PurCem (AB) + 19/20/22/29 NA PurCem (C) Combined

: < 10 g/l NA PurCem (AB) + 31 NA PurCem (C) Combined

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : no data available

Incompatible materials : no data available

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : Harmful if inhaled.

Acute dermal toxicity : no data available

Print Date 03/17/2014

Ingredients:

Revision Date 03/17/2014

Diphenylmethanediisocyanate, isomeres and homologues: Acute oral toxicity : LD50 Oral rat: > 10,000 mg/kg

: Acute toxicity estimate : 1.5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

: LD50 Dermal rabbit: > 9,400 mg/kg Acute dermal toxicity

Skin corrosion/irritation

Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

Causes serious eye irritation.

Respiratory or skin sensitization

Product

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : no data available

IARC not applicable **NTP** not applicable

Reproductive Toxicity/Fertility

Product

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Revision Date 03/17/2014 Print Date 03/17/2014

Assessment: May cause respiratory irritation.

STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Product

Assessment: May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Product

no data available

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Revision Date 03/17/2014 Print Date 03/17/2014

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Diphenylmethanediisocyana 9016-87-9 40.00 %

te, isomeres and homologues

Clean Air Act

Ozone-Depletion

Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 This product does not contain any chemicals known to the State

of California to cause cancer, birth, or any other reproductive

defects.

16. Other information

Revision Date 03/17/2014

Print Date 03/17/2014

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/17/2014

Material number: 462200

Revision Date 03/18/2014 Print Date 03/18/2014

1. Identification

Product name Sikafloor®-29 NA PurCem® Part C

Supplier Sika Corporation

Address 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on

use

For further information, refer to the product technical data

sheet.

2. Hazards identification

GHS Classification

Skin irritation, Category 2 H315: Causes skin irritation. Serious eye damage, Category 1 H318: Causes serious eye damage.

Carcinogenicity, Category 1A

H350: May cause cancer.

GHS Label element

Hazard pictograms





Signal Word Danger

Hazard Statements : H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

Revision Date 03/18/2014

Print Date 03/18/2014

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

P310 Immediately call a POISON CENTER or doctor/

physician.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 50 - <= 100 %
Portland cement	65997-15-1	>= 10 - < 20 %
Quartz (SiO2) <5µm	14808-60-7	>= 0 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

: Small amounts splashed into eyes can cause irreversible In case of eye contact

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Revision Date 03/18/2014 Print Date 03/18/2014

Most important symptoms and effects, both acute and

delaved

: Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

irritant effects carcinogenic effects

Protection of first-aiders

: Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician

: Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

 Revision Date 03/18/2014
 Print Date 03/18/2014

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : no data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO2+2 total dust
		OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
Portland cement	65997-15-1	ACGIH	TWA	1 mg/m3 Respirable fraction
		OSHA P0	TWA	10 mg/m3 Total
		OSHA P0	TWA	5 mg/m3 Respirable fraction
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA Z-3	TWA	50 Million particles per cubic foot Dust

Revision Date 03/18/2014 Print Date 03/18/2014

		1		
Quartz (SiO2) <5µm	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO2+2 total dust
		OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

Revision Date 03/18/2014 Print Date 03/18/2014

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

9. Physical and chemical properties

Appearance : powder Color : gray

Odor : odorless

Odor Threshold : no data available

Flash point : Note: not applicable

Ignition temperature : no data available

Decomposition temperature : no data available

Lower explosion limit (Vol%) : no data available

Upper explosion limit (Vol%) : no data available

Flammability (solid, gas) : no data available

Oxidizing properties : no data available

Autoignition temperature : no data available

pH : Note: not applicable

Melting point/range /

Freezing point

: no data available

Boiling point/boiling range : no data available

Vapor pressure : no data available

Density : ca.2.8 g/cm3

at 73 °F (23 °C)

Water solubility : Note: insoluble

Safety Data Sheet



Sikafloor®-29 NA PurCem® Part C

Revision Date 03/18/2014 Print Date 03/18/2014

Partition coefficient: n-

octanol/water

: no data available

Viscosity, dynamic

: no data available

Viscosity, kinematic

Note: not applicable

Relative vapor density

no data available

Evaporation rate

no data available

Burning rate

no data available

Volatile organic compounds

(VOC) content

: < 5 g/l NA PurCem (AB) + 29 NA PurCem (C) Combined

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

: Stable under recommended storage conditions.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: no data available

Conditions to avoid

: no data available

11. Toxicological information

Incompatible materials

Acute toxicity

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation

Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

Causes serious eye damage.

Respiratory or skin sensitization

Revision Date 03/18/2014

Print Date 03/18/2014

Product

no data available

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : May cause cancer.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

Quartz (SiO2) <5µm 14808-60-7

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7 Quartz (SiO2) <5µm 14808-60-7

Reproductive Toxicity/Fertility

Product

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Assessment: no data available

STOT-repeated exposure

Prolonged exposure can cause silicosis.

Product

Assessment: no data available

Aspiration toxicity

Product

no data available

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Revision Date 03/18/2014 Print Date 03/18/2014

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

Safety Data Sheet

Sikafloor®-29 NA PurCem® Part C

Revision Date 03/18/2014 Print Date 03/18/2014

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 WARNING! This product contains a chemical known in the

State of California to cause cancer.

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive

harm.

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

Revision Date 03/18/2014

Print Date 03/18/2014

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/18/2014

Material number: 462184