Revision Date 04/04/2014 Print Date 04/04/2014

1. Identification

Product name : Sikafloor® 340 Part A

Supplier : Sika Corporation

Address : 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the chemical and restrictions on

chemical and restrictions on use

For further information, refer to the product technical data

sheet.

2. Hazards identification

GHS Classification

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

GHS Label element

Hazard pictograms

Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

alcohol-resistant foam for extinction.

Disposal:

P501 Dispose of contents/ container to an approved waste

Print Date 04/04/2014

disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
2-methoxy-1-methylethyl acetate	108-65-6	>= 25 - < 50 %
tert-butyl acetate	540-88-5	>= 5 - < 10 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects

and symptoms.

No known significant effects or hazards.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Revision Date 04/04/2014 Print Date 04/04/2014

Suitable extinguishing media

: Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

Specific extinguishing

methods

: Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

: Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapors accumulating to form explosive

concentrations. Vapors can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

7. Handling and storage

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage

Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

Store in accordance with local regulations.

Revision Date 04/04/2014

Sikafloor® 340 Part A

Materials to avoid : no data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
tert-butyl acetate	540-88-5	ACGIH	TWA	200 ppm
		OSHA Z-1	TWA	200 ppm 950 mg/m3
		OSHA P0	TWA	200 ppm 950 mg/m3

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Print Date 04/04/2014

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

: Safety eyewear complying with an approved standard should Eye protection

Revision Date 04/04/2014 Print Date 04/04/2014

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment

before entering eating areas.

9. Physical and chemical properties

Appearance : liquid

Color : amber

clear

Odor : characteristic

Odor Threshold : no data available

Flash point : 115 °F (46 °C)

Ignition temperature : no data available

Decomposition temperature : no data available

Lower explosion limit (Vol%) : 1.5 %(V)

Upper explosion limit (Vol%) : 10.8 %(V)

Flammability (solid, gas) : no data available

Oxidizing properties : no data available

Autoignition temperature : no data available

pH : Note: not applicable

Melting point/range /

Freezing point

: no data available

Boiling point/boiling range : no data available

Vapor pressure : 0.025 mmHg (0.0337 hpa)

Density : ca.1.04 g/cm3

at 73 °F (23 °C)

Water solubility : Note: partly soluble

Partition coefficient: n-

octanol/water

no data available

Safety Data Sheet



Sikafloor® 340 Part A

Revision Date 04/04/2014 Print Date 04/04/2014

Viscosity, dynamic : no data available

Viscosity, kinematic : ca.> 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : no data available

Evaporation rate : no data available

Burning rate : no data available

Volatile organic compounds : 279 g/l

(VOC) content

A+B Combined

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : no data available

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Ingredients:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral rat: > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: > 5,000 mg/kg

Skin corrosion/irritation

Product

no data available

Serious eye damage/eye irritation

Product

no data available

Revision Date 04/04/2014

Respiratory or skin sensitization

Product

no data available

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : no data available

IARC not applicable NTP not applicable

Reproductive Toxicity/Fertility

Product

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Assessment: no data available

STOT-repeated exposure

Product

Assessment: no data available

Aspiration toxicity

Product

no data available

Revision Date 04/04/2014 Print Date 04/04/2014

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

UN number 1263
Description of the goods Paint
Class 3
Packing group III
Labels 3
Emergency Response 128
Guidebook Number

IATA

UN number 1263
Description of the goods Paint
Class 3
Packing group III
Labels 3
Packing instruction (cargo 366

aircraft)

Packing instruction 355

(passenger aircraft)

Packing instruction Y344

(passenger aircraft)

IMDG

UN number 1263
Description of the goods PAINT
Class 3
Packing group III
Labels 3
EmS Number 1 F-E
EmS Number 2 S-E

Revision Date 04/04/2014 Print Date 04/04/2014

Marine pollutant no

DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated. IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

> components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

Ozone-Depletion

This product neither contains, nor was manufactured with a **Potential** Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 This product does not contain any chemicals known to the State

of California to cause cancer, birth, or any other reproductive

defects.

16. Other information

Revision Date 04/04/2014

HMIS Classification



Print Date 04/04/2014

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/04/2014

Material number: 187913

Revision Date 05/16/2014 Print Date 05/16/2014

1. Identification

Product name : Sikafloor® 340 ESD Part B

Supplier : Sika Corporation

Address : 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on use

For further information, refer to the product technical data

sheet.

2. Hazards identification

GHS Classification

Acute toxicity, Category 4 (Inhalation) H332: Harmful if inhaled.

Respiratory sensitization, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary Statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves.

P285 In case of inadequate ventilation wear respiratory

protection. Response:

Revision Date 05/16/2014 Print Date 05/16/2014

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 IF INHALED: Remove victim to fresh air and keep

at rest in a position comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Aliphatic polyisocyanate	28182-81-2	>= 50 - <= 100 %
hexamethylene-di-isocyanate	822-06-0	>= 0 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

: sensitizing effects

delayed

Asthmatic appearance Respiratory disorder Allergic reactions

Headache

See Section 11 for more detailed information on health effects

Revision Date 05/16/2014 Print Date 05/16/2014

and symptoms.

Protection of first-aiders Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures **Environmental precautions** : Use personal protective equipment. Deny access to unprotected persons.

Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

Revision Date 05/16/2014 Print Date 05/16/2014

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

Materials to avoid : no data available

8. Exposure controls/personal protection

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any

recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Revision Date 05/16/2014 Print Date 05/16/2014

9. Physical and chemical properties

Appearance liquid Color clear

Odor odorless

Odor Threshold no data available

Flash point 338 °F (170 °C)

Ignition temperature not applicable

Decomposition temperature no data available

Lower explosion limit (Vol%) no data available

Upper explosion limit (Vol%) no data available

Flammability (solid, gas) no data available

Oxidizing properties no data available

Autoignition temperature no data available

pН Note: not applicable

Melting point/range /

Freezing point

Boiling point/boiling range no data available

Vapor pressure no data available

ca.1.12 g/cm3 Density

at 73 °F (23 °C)

no data available

Water solubility Note: insoluble

Partition coefficient: n-

octanol/water

no data available

Viscosity, dynamic

no data available

Viscosity, kinematic > 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density no data available

Evaporation rate no data available

Burning rate no data available

Volatile organic compounds

(VOC) content

367 g/l

A+B+D+E Combined

Revision Date 05/16/2014 Print Date 05/16/2014

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : no data available

Incompatible materials : no data available

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : Harmful if inhaled.

Acute dermal toxicity : no data available

Ingredients:

hexamethylene-di-isocyanate:

Acute oral toxicity : LD50 Oral rat: 746 mg/kg

Acute inhalation toxicity : LC50 rat: 0.124 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal rat: > 7,000 mg/kg

Skin corrosion/irritation

Product

no data available

Serious eye damage/eye irritation

Product

no data available

Respiratory or skin sensitization

Product

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Revision Date 05/16/2014

Print Date 05/16/2014

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : no data available

NTP not applicable not applicable

Reproductive Toxicity/Fertility

Product

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Assessment: no data available

STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Product

Assessment: no data available

Aspiration toxicity

Product

no data available

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal methods

Revision Date 05/16/2014 Print Date 05/16/2014

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Revision Date 05/16/2014

Print Date 05/16/2014

Clean Air Act

Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 05/16/2014

Revision Date 05/16/2014

Print Date 05/16/2014

Material number: 418738