

# MATERIAL SAFETY DATA SHEET



Date Issued: 05/03/2009  
 MSDS No: Sikafloor 700 ESD Part H  
 Date-Revised: 05/17/2009  
 Revision No: 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**GENERAL USE:** Hardner  
**PRODUCT DESCRIPTION:** Sikafloor 700 ESD Part H  
**PRODUCT CODE:** Sikafloor 700 ESD Part H

### MANUFACTURER

Sika Corporation, Operations  
 www.sikacorp.com  
 201 Polito Avenue  
 Lyndhurst NJ 07071  
**Service Number:** 201-933-8800  
**Alternate Customer Service:** Fax: 201-804-1076

### SUPPLIER

Sika Corporation, Construction  
 www.sikaconstruction.com  
 201 Polito Avenue  
 Lyndhurst NJ 07071  
**Product Stewardship:** 201-933-8800

### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation) :**(800) 424 - 9300  
**CHEMTREC (International) :**(703) 527 - 3887

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Amber Liquid

**IMMEDIATE CONCERNS:** Caution! Corrosive to eyes. Corrosive to skin. Severe eye irritant. Severe skin irritant. May cause respiratory sensitization. May cause skin sensitization. Keep away from heat and source of ignition.

### POTENTIAL HEALTH EFFECTS

**EYES:** Material (including vapors) may cause eye irritation, burns or even blindness.

**SKIN:** Causes skin burns.

**SKIN ABSORPTION:** If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.

**INGESTION:** If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

**INHALATION:** Inhalation of aerosol may cause irritation to the upper respiratory tract. Can cause severe eye, skin and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors in high concentrations may cause irritation of respiratory system.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**CHRONIC EFFECTS:** This product contains no listed carcinogens according to IARC, ACGIH, NTP, and/or OSHA in concentrations of 0.1 percent or greater. Repeated or prolonged contact causes sensitization, asthma and eczemas. Prolonged contact may result in chemical burns and permanent damage.

**MEDICAL CONDITIONS AGGRAVATED:** Eye disease, Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or corrosion). Adverse eye effects (such as conjunctivitis or corneal damage). Asthma. Adverse respiratory effects (such as cough, tightness of chest or shortness of breath).

**ROUTES OF ENTRY:** Inhalation, Skin Contact, Eye Contact

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt. %	CAS	EINECS
Proprietary Blend of Aliphatic and Cycloaliphatic Amines	20 - 60	Mixture	N/A
Benzyl alcohol	20 - 30	100-51-6	202-859-9

**COMMENTS:** The criteria for listing components in the composition section are as follows: Carcinogens are listed when present at 0.1% or greater; components which are otherwise hazardous according to OSHA are listed when present at 1.0% or greater; non-hazardous components are not listed. This is not intended to be complete compositional disclosure. Refer to section 15 for applicable states right to know and other regulatory information.

**4. FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water for two to three minutes. Remove any contact lenses and continue flushing for 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention.

**SKIN:** Remove contaminated clothing including shoes and immediately wash affected area with plenty of soap and water. Seek medical attention. Wash contaminated clothing and shoes before reuse.

**INGESTION:** If victim is conscious and alert, give 2-3 glasses of water to drink and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. Seek immediate medical attention. Do not leave victim unattended. Vomiting may occur spontaneously. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.

**INHALATION:** Remove to fresh air away from further exposure provide oxygen if breathing is difficult. Keep warm and at rest. If cough or other symptoms develop, seek medical attention.

**5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Dry Chemical, Foam or Carbon Dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

**HAZARDOUS COMBUSTION PRODUCTS:** May generate ammonia gas. May generate toxic nitrogen oxide gases. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure demand (MSHA/NIOSH approved or equivalent) and full protective gear. Toxic vapors may evolve. Fight fires from a safe distance or protected areas. Use of large volumes of water may produce run-off that could be toxic to wildlife and/or pose a hazardous waste disposal issue. Water may not be effective for large fires.

**FIRE FIGHTING EQUIPMENT:** Respiratory and eye protection are required for fire fighting personnel. Full protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of a SCBA may not be required.

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Absorb with inert material. Clean up and dispose of at an appropriate waste disposal facility.

**LARGE SPILL:** Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material.

Wearing the appropriate personal protective equipment designated in Section 8, close or cap valves and/or block or plug hole in leaking container and transfer to another container.

Contain material as described above and call the local fire or police department for immediate emergency assistance.

**ENVIRONMENTAL PRECAUTIONS**

**LAND SPILL:** Use appropriate containment to avoid runoff or release to ground.

**GENERAL PROCEDURES:** Absorb on diatomaceous earth or equivalent inert material. Shovel up and dispose of at an appropriate waste disposal facility according to current applicable laws and regulations, and product characteristics at time of disposal.

**7. HANDLING AND STORAGE**

**HANDLING:** Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer causing nitrosamines could be formed. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.

**STORAGE:** Store in unopened containers under cool and dry conditions.

Do not store with, or close to strong acids.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Benzyl alcohol	TWA	N.E. [1]	N.E. [1]	N.E. [1]	N.E. [1]	N.E. [1]	N.E. [1]
	STEL	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
<b>OSHA TABLE COMMENTS:</b>							
1. N.E. = None Established							

**ENGINEERING CONTROLS:** Good industrial hygiene practice dictates that worker protection should be achieved through engineering controls, such as ventilation, whenever feasible. When such controls are not feasible to achieve full protection, the use of respirators and other personal protective equipment is mandated. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Amber Liquid

**pH:** Alkaline

**10. STABILITY AND REACTIVITY**

**STABLE:** Yes

**HAZARDOUS DECOMPOSITION PRODUCTS:** Nitric Acid

Ammonia

Nitrogen oxides

Nitrogen oxide can react with water vapors to form corrosive nitric acid

Carbon monoxide

Carbon dioxide

Aldehydes

**INCOMPATIBLE MATERIALS:** Amines

Incompatible with bases  
Reducing Agents  
Oxidizing Agents

## 11. TOXICOLOGICAL INFORMATION

### CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
Benzyl alcohol	Not Listed	Not Listed	Not Listed

**IARC:** Not listed by IARC

**NTP:** Not listed by NTP

**OSHA:** Not listed by OSHA

**SENSITIZATION:** May be sensitizing to the skin.

**COMMENTS:** To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** No data is available on the product itself.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Mix multi-component materials together and allow to harden. Dispose of waste at an appropriate waste disposal facility according to current applicable laws and regulations.

**GENERAL COMMENTS:** Refer to Section 6, Accidental Release Measures for additional information.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Paint

**PRIMARY HAZARD CLASS/DIVISION:** 8

**UN/NA NUMBER:** 3066

**PACKING GROUP:** III

**NAERG:** 153

**LABEL:** Corrosive

### AIR (ICAO/IATA)

**SHIPPING NAME:** Paint

**UN/NA NUMBER:** 3066

**PRIMARY HAZARD CLASS/DIVISION:** 8

**PACKING GROUP:** III

**LABEL:** Corrosive

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Paint

**UN/NA NUMBER:** 3066

**PRIMARY HAZARD CLASS/DIVISION:** 8

**PACKING GROUP:** III

**LABEL:** Corrosive

**CANADA TRANSPORT OF DANGEROUS GOODS**

**SHIPPING NAME:** Paint

**UN/NA NUMBER:** 3066

**PRIMARY HAZARD CLASS/DIVISION:** 8

**PACKING GROUP:** III

**CANUTEC GUIDE:** 153

**LABEL:** Corrosive

**15. REGULATORY INFORMATION**

**UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**ACUTE:** Yes

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA REGULATORY:** All intentional ingredients are listed on the TSCA Inventory.

**CALIFORNIA PROPOSITION 65:** (component (s) know to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986"): None

**INTERNATIONAL REGULATIONS:**

**EINECS Inventory Status:**

This product, or its components, are listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS).

**Canadian Inventory Status:**

This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL).

**Australian Inventory Status:**

This product, or its components, are listed on or are exempt from the Australian Inventory of Chemical Substances (AICS).

**GENERAL COMMENTS:** EU Additional Classification:

Symbol of Danger: Xn(Harmful) C(Corrosive)

R 20/22 Harmful by inhalation and if swallowed.

R 34 Causes burns

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection

**16. OTHER INFORMATION**

**TITLE:** MSDS Coordinator

**REVISION SUMMARY:** Revision #: 1. This MSDS replaces the May 03, 2009 MSDS.

## HMIS RATING

<b>HEALTH:</b>	<b>3</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	<b>G</b>

**MANUFACTURER DISCLAIMER:** The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESSED OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikscorp.com](http://www.sikscorp.com) or 201-933-8800.

# MATERIAL SAFETY DATA SHEET



Date Issued: 05/03/2009  
 MSDS No: Sikafloor 700 ESD Part R  
 Date-Revised: 05/17/2009  
 Revision No: 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION:** Sikafloor 700 ESD Part R  
**PRODUCT CODE:** Sikafloor 700 ESD Part R

### MANUFACTURER

Sika Corporation, Operations  
 www.sikacorp.com  
 201 Polito Avenue  
 Lyndhurst NJ 07071  
**Service Number:** 201-933-8800  
**Alternate Customer Service:** Fax: 201-804-1076

### SUPPLIER

Sika Corporation, Construction  
 www.sikaconstruction.com  
 201 Polito Avenue  
 Lyndhurst NJ 07071  
**Product Stewardship:** 201-933-8800

### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation) :**(800) 424 - 9300  
**CHEMTREC (International) :**(703) 527 - 3887

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Blue Liquid

**IMMEDIATE CONCERNS:** CAUTION! May cause eye, skin, and respiratory tract irritation; May cause allergic skin reaction.

### POTENTIAL HEALTH EFFECTS

**EYES:** May cause eye irritation.

**SKIN:** May cause irritation and sensitization of the skin.

**INGESTION:** Will cause illness

**INHALATION:** May cause irritation of the respiratory tract.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**CARCINOGENICITY:** This product contains an ingredients designated IARC as probable human carcinogens:  
 Crystalline Silica

**MEDICAL CONDITIONS AGGRAVATED:** Individuals who are sensitized to isocyanates and those with asthma, respiratory disorder, skin allergies, and eczema.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS
Modified Epoxy Resin	60 - 90	Mixture	N/A
Tin Antimony Oxide	5 - 15	68187-54-2	269-105-9
MICA	5 - 10	12001-26-2	N/A
Silica, crystalline	5 - 10	14808-60-7	238-878-4
Hydrocarbon resin	5 - 10	25155-81-1	N/A

**COMMENTS:** The criteria for listing components in the composition section are as follows: Carcinogens are listed when present at 0.1% or greater; components which are otherwise hazardous according to OSHA are listed when present at 1.0% or greater; non-hazardous components are not listed. This is not intended to be complete compositional disclosure. Refer to section 15 for applicable states right to know and other regulatory information.

#### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for two to three minutes. Remove any contact lenses and continue flushing for 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention.

**SKIN:** Wash with soap and water. If irritation persists see a physician.

**INGESTION:** Seek medical attention if large amounts are swallowed.

**INHALATION:** Remove to fresh air away from further exposure provide oxygen if breathing is difficult. Keep warm and at rest. If cough or other symptoms develop, seek medical attention.

#### 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** (230°F) Penskey-Marten CC

**EXTINGUISHING MEDIA:** Dry Chemical, Foam, Carbon Dioxide (CO<sub>2</sub>), Water Spray

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Absorb with inert material. Clean up and dispose of at an appropriate waste disposal facility.

**LARGE SPILL:** Evacuate Area. Absorb with inert material. Clean up spill and dispose of at an approved disposal facility.

#### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Keep product in original container. Store in cool, dry well ventilated area.

**HANDLING:** Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION



**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Tin Antimony Oxide	TWA	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
	STEL	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
MICA	TWA	N.E.	2.5 mg/m <sup>3</sup>	N.E.	N.E.	N.E.	N.E.
	STEL	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Silica, crystalline	TWA	N.E. <sup>[1]</sup>	(0.1) mg/m <sup>3</sup> <sup>[1]</sup>	N.E. <sup>[2]</sup>	0.05 mg/m <sup>3</sup> <sup>[2]</sup>	N.E.	N.E.
	STEL	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Hydrocarbon resin	TWA	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
	STEL	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
<b>OSHA TABLE COMMENTS:</b>							
1. 8 hours Form: Respirable dust							
2. 8 hours. Form: Respirable fraction							

**ENGINEERING CONTROLS:** Good industrial hygiene practice dictates that worker protection should be achieved through engineering controls, such as ventilation, whenever feasible. When such controls are not feasible to achieve full protection, the use of respirators and other personal protective equipment is mandated. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Wear safety glasses with side shields or goggles when handling this material.

**SKIN:** Wear chemical resistant (impervious) gloves.

**RESPIRATORY:** Organic chemical cartridge respirator, if needed.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**ODOR:** Epoxy

**APPEARANCE:** Blue Liquid

**VAPOR DENSITY:** Heavier than air

**FLASHPOINT AND METHOD:** (230°F) Penskey-Martens CC

**SOLUBILITY IN WATER:** Partially Soluble

**EVAPORATION RATE:** Is slower than Butyl Acetate

**10. STABILITY AND REACTIVITY**

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** The product is stable under normal ambient conditions of temperature and pressure.

**CONDITIONS TO AVOID:** Excessive heat, open flames, sparks.

**INCOMPATIBLE MATERIALS:** Strong acids, bases, oxidizing agents, mercaptans, and amines under uncontrolled conditions.

## 11. TOXICOLOGICAL INFORMATION

**EYE EFFECTS:** This material may cause irritation to the eyes.

**SKIN EFFECTS:** This material may cause sensitization and irritation to the skin.

### CARCINOGENICITY

**IARC:** The agents (mixture) is possible carcinogen to humans. The exposure circumstances entails exposures that are possibly carcinogen to humans:  
Crystalline Silicate (respirable form)

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** No data is available on the product itself.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of according to all federal, state and local regulations.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated

### ROAD AND RAIL (ADR/RID)

**PROPER SHIPPING NAME:** Not Regulated

### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Not Regulated

### CANADA TRANSPORT OF DANGEROUS GOODS

**SHIPPING NAME:** Not Regulated

## 15. REGULATORY INFORMATION

### UNITED STATES

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA REGULATORY:** All intentional ingredients are listed on the TSCA Inventory.

**CALIFORNIA PROP 65 WARNING:** This product contains a chemical known to the State of California to cause cancer.

### INTERNATIONAL REGULATIONS:

#### EINECS Inventory Status:

This product, or its components, are listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS).

#### Canadian Inventory Status:

This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL).

#### Australian Inventory Status:

This product, or its components, are listed on or are exempt from the Australian Inventory of Chemical Substances (AICS).

**GENERAL COMMENTS:**

EU Additional Classification

Symbol of Danger: Xi (Irritant)

R: 36/38 Irritating to eyes and skin.

R: 43 May cause sensitization by skin contact.

S: 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

**16. OTHER INFORMATION**

**TITLE:** MSDS Coordinator

**REVISION SUMMARY:** Revision #: 1. This MSDS replaces the May 03, 2009 MSDS.

**HMIS RATING**

<b>HEALTH:</b>	<b>2</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	<b>G</b>

**MANUFACTURER DISCLAIMER:** The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESSED OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikscorp.com](http://www.sikscorp.com) or 201-933-8800.