W. R. MEADOWS. SEATTIGHT.

SAFETY DATA SHEET

							Pag	e 1 of 2			
•		SECTION 1:	PRODUCT AND C	OMPANY	IDENTIFICAT	ON	-				
Product:	POLY-JET®	[®] LOX	Pa	art Number:	: 4340000						
Manufacturer:						300 Industrial Drive Hampshire, Illinois 60140					
Telephone:	(847) 214-2	2100		In c	• •	ency, dial (800) 424-	-9300 (CHEMTRE	C)			
Revision Date:	9/9/2014										
Product Use:	One Part P	olysulfide Gun-Gra									
SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS											
HMIS		HAZARD STATE	EMENTS								
Health	2	WARNING!									
Flammability	1 May cause skin/eye irritation.										
Reactivity Personal Protection		0 PRECAUTIONARY STATEMENTS Avoid direct contact.									
	Avoid breathing aerosols/sprays. SECTION 3: HAZARDS COMPONENTS										
				SARA	Vapor Pro	essure LEL					
Chemical Name:		CAS Number	<u>% by Weight</u>	313	(mm Hg@		2)				
1. Polysulfide Polymer		68611-50-7	30-40	No	N/E		-				
2. Barium Peroxide		1304-29-6	1-10	Yes	N/E						
3. Titanium Dioxide		13463-67-7	1-10	No	N/E	E N/E					
This product contains Talc (CAS# 14807-96-6). Prolonged exposure to excessive airborne concentrations of Talc can result in lung scarring. Talc											
contains crystalline silica as a naturally occuring component. Exposure to silica is not expected to occur as the product is supplied as a solution.											
If product is dry/abraded, appropriate protective measures should be taken to control exprosure to airborne silica. Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40											
CFR Part 372, chemicals lis	ted on the 31						N/A: Not Applicab	ole			
SECTION 4: EMERGENCY AND FIRST AID PROCEDURES											
EYE CONTACT: Move victim from exposure source. Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention. SKIN CONTACT: Remove contaminated shoes/clothing. Wash affected areas with mild soap and water. If symptoms persist, seek medical											
attention.											
INHALATION: Move victim	n from expos	ure source and tre	et symptoms If sy	motoms ne	rsist seek mer	lical attention					
INGESTION: Seek immedia							m's head below th	he			
hips to prevent lung aspira				0111111-0 -1							
		SECTIO	N 5: FIRE AND E	XPLOSIVES	HAZARDS						
FLASHPOINT: > 210 degre	es F										
EXTINGUISHING MEDIA: \	Water fog, fo	am, dry chemical,	and carbon dioxide	e.							
CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products may be emitted.											
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Use of full fire protection ensemble with SCBA is recommended.											
SECTION 6: ACCIDENTAL RELEASE MEASURES											
SPILL OR LEAK PROCEDUR	ES: Evacuate	area of unprotec	ted personnel. Dike	e/contain sp	oilled material.	Take up with an ap	propriate absorb	ent			
and place in sealed/marked	d containers										
			TION 7: HANDLIN	NG AND ST	ORAGE						
SAFE HANDLING PROCEDU											
SAFE STORAGE: Keep containers closed when not in use. Store in cool/dry location.											
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION OSHA ACGIH											
Chemical Name:	PEL	O: PEL/CEILING	SHA PEL/STEL	<u>SKIN</u>	TWA	ACGII <u>TLV/CEILING</u>	H <u>TLV/STEL</u>	SKIN			
1. Polysulfide Polymer	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E			
2. Barium Peroxide*	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E			
3. Titanium Dioxide*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
	N/E: Not Esta				ided as materi	als are in suspensio	n.				
	ENGINEERING CONTROLS: None normally required under normal use conditions.										
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.											

	SAFETY DAT	TA SHEET
Date of Preparation: 9/9/14	Page 2	of 2 4340000
	SECTION 9: PHYSICAL AND	CHEMICAL PROPERTIES
BOILING POINT: 250 degrees F	VAPOR DENSITY: >1 (Air=1)	% VOLATILE BY VOLUME: Not Applicable
EVAPORATION RATE: <1 (Ether=1)	pH LEVEL: N/A	% VOLATILE BY WEIGHT: Not Applicable
WEIGHT PER GALLON: 11.88 (Average)	PRODUCT APPEARANCE: Heavy Li	quid VOC CONTENT: 12 g/L
	SECTION 10: STABIL	ITY/REACTIVITY
STABILITY: Stable.	HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS AND MATERIALS TO AVO		
HAZARDOUS DECOMPOSITION PRODU		de, and incomplete combustion products.
	SECTION 11: TOXICOLOG	ICAL INFORMATION
EYE CONTACT: Direct contact may cause		
SKIN CONTACT: Direct contact may resu		
INHALATION: Not expected to be an ex		
INGESTION: Not expected to be an expo		
		dness, and swelling. Symptoms of skin irritation include reddening,
		nose, chest discomfort, shortness of breath, and reduced lung
		nal pain, nausea, vomiting, and diarrhea.
		v disorders may be aggravated by exposure to this product.
OTHER HEALTH EFFECTS: Barium comp		
	SECTION 12: ECOLOGI	
ECOTOXICITY: Not Established	DEGRADABILITY: N	
SOIL MOBILITY: N/E	OTHER ADVERSE EFFECTS: N	
	SECTION 13: WASTE DISF	
WASTE DISPOSAL INFORMATION: Non	-hazardous material for waste dispos	al purposes. Solid product can be landfill disposed.
	SECTION 14: TRANSPORT	ATION INFORMATION
HAZARDOUS/NON-HAZARDOUS MATE	RIAL: Non-hazardous.	
UN NUMBER: None.	HAZARD CLASS: None.	PACKING GROUP: None.
UN PROPER SHIPPING NAME: Not regu	lated.	
ENVIRONMENTAL HAZARDS: Not deter	mined.	
BULK TRANSPORTATION INFORMATIO	N: Not applicable; product is not ship	oped in bulk.
SPECIAL PRECAUTIONS: None recog	nized.	
	SECTION 15: REGULAT	DRY INFORMATION
OTHER REGULATORY CONSIDERATIONS	S: None.	
	SECTION 16: OTHER	INFORMATION
PREPARATION DATE: 9/9/2014		

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.